

## VG H M32 MS

**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

### Similar to illustration



In addition to the extensive range of enclosures, Weidmüller offers a variety of cable glands for a wide range of applications.

The cable glands made of brass, plastic and stainless steel meet the most various IP protection classes to suit any industrial enclosure.

Depending on the series of cable glands and the application, the cable glands are approved and tested according to VDE, UL, UR, cULus, DNV GL or EN 45545.

### General ordering data

|                 |   |
|-----------------|---|
| Version         | VG H (HDC halved cable gland), Cable glands, straight, M 32, OD min. 16 - OD max. 25 mm, IP65, Brass, nickel-plated |
| Order No.       | <a href="#">1921760000</a>  |
| Type            | VG H M32 MS   |
| GTIN (EAN)      | 4032248563029   |
| Qty.            | 20 pc(s).   |
| Available until | 2015-10-30  |

## VG H M32 MS

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

[info@weidmueller.com](mailto:info@weidmueller.com)

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Dimensions and weights

|            |         |                |           |
|------------|---------|----------------|-----------|
| Width      | 32 mm   | Width (inches) | 1.26 inch |
| Net weight | 27.15 g |                |           |

### Temperatures

|                       |                |
|-----------------------|----------------|
| Operating temperature | -20 °C...60 °C |
|-----------------------|----------------|

### Environmental Product Compliance

|            |                |      |                                      |
|------------|----------------|------|--------------------------------------|
| REACH SVHC | Lead 7439-92-1 | SCIP | b5ff1f66-ddba-4739-9fc0-0521ddb52139 |
|------------|----------------|------|--------------------------------------|

### General information

|                                      |              |                                      |                      |
|--------------------------------------|--------------|--------------------------------------|----------------------|
| AF size                              | 32 mm        | AF size 1                            | 32 mm                |
| Cable glands                         | metric, M 32 | External thread                      | M 32                 |
| Halogen                              | Yes          | Material                             | Brass, nickel-plated |
| Notch multi-layer sealing diameter 1 | 16 mm        | Notch multi-layer sealing diameter 2 | 19 mm                |
| Notch multi-layer sealing diameter 3 | 22 mm        | Notch multi-layer sealing diameter 4 | 25 mm                |
| O-Ring                               | NBR          | Operating temperature range, max.    | 60 °C                |
| Operating temperature range, min.    | -20 °C       | Outer cable diameter, max.           | 25 mm                |
| Outer cable diameter, min.           | 16 mm        | Pitch of thread                      | 1.5 mm               |
| Protection degree                    | IP65         | Protection degree with GWDR          | IP65                 |
| Sealing                              | NBR          |                                      |                      |

### Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000441    | ETIM 7.0    | EC000441    |
| ETIM 8.0    | EC000441    | ECLASS 9.0  | 27-14-44-32 |
| ECLASS 9.1  | 27-14-44-32 | ECLASS 10.0 | 27-14-44-32 |
| ECLASS 11.0 | 27-14-44-32 | ECLASS 12.0 | 27-14-08-01 |

### Approvals

Approvals



ROHS

Conform

### Downloads

|                  |  |
|------------------|--|
| Engineering Data | <a href="#">EPLAN, WSCAD</a>             |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |
| Brochures        |  |