



### Main

|                                   |   |
|-----------------------------------|---|
| Range of Product                  | 9012G   |
| Pressure sensor type              | Electromechanical pressure switch   |
| Pressure sensor name              | 9012G   |
| Pressure Rating                   | 1000 psi (6894.76 kPa)  |
| Maximum pressure                  | 1000 psi  |
| Contacts type and composition     | NC-NO, 2 SPDT-DB, Form Z, snap action, silver nickel contacts                                   |
| Controlled fluid                  | Hydraulic oil -15...250 °F (-26...121 °C))<br>Non-corrosive liquids<br>Air<br>Non-corrosive gas |
| Fluid connection type             | 0.44 inch 20 UNF-2B UL 508  |
| Pressure switch type of operation | Detection of 1 single threshold   |
| Scale type                        | Fixed   |
| Local display                     | Without   |

### Complementary

|                                      |  |
|--------------------------------------|--|
| Range on decreasing pressure         | 20...1000 psi (137.90...6894.76 kPa)                                       |
| Approx fix differential at mid range | 59 psi (406.79 kPa) +/- 2.5 % full scale                                   |
| Terminal block type                  | 4 screw terminals  |
| Electrical connection                | 1 male connector mini) 5 pins  |
| Terminal identifier                  | (1-5)NC<br>(3)Gnd<br>(2-4)NO   |
| Electrical circuit type              | Control circuit  |
| Local signalling                     | 1 LED red) 120 V AC 105...125 V)   |
| Line Rated Current                   | 0.22 A 125 V DC<br>3 A 120 V AC  |
| Setting                              | Internal   |
| Enclosure Material                   | Die cast aluminium alloy 380   |
| Pressure actuator                    | Piston   |
| Height                               | 6.24 in (158.50 mm)  |
| Depth                                | 4.56 in (115.82 mm)  |
| Width                                | 5.05 in (128.27 mm)  |
| Operating position                   | Any position   |
| Materials in contact with fluid      | 440 stainless steel<br>Viton fluorocarbon<br>Teflon<br>303 stainless steel |
| Short-circuit protection             | 10 A cartridge overload and short-circuit protection gL                    |
| Maximum operating rate               | 120 cyc/mn   |
| Mechanical durability                | 3000000 cycles   |
| Repeat accuracy                      | 4 %  |
| Net Weight                           | 3 lb(US) (1.36 kg)   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|                                       |   |
|---------------------------------------|---|
| Vibration resistance                  | 2 gn 40...150 Hz)IEC 68-2-6                                       |
| Shock resistance                      | 50 gn IEC 58-2-27   |
| Standards                             | CE<br>CSA C22.2 No 14<br>UL 508                                   |
| Product Certifications                | UL listed file E12158 CCN NKPZ<br>CE<br>CSA LR25490 class 3211 03 |
| NEMA degree of protection             | NEMA 4/4X/13 UL 50  |
| Ambient Air Temperature for Operation | -10...185 °F (-23...85 °C)  |

## Ordering and shipping details

|                       |   |
|-----------------------|---|
| Category              | 21522-9012 G INDUSTRIAL PRESSURE SWITCHES |
| Discount Schedule     | CP7G                                      |
| GTIN                  | 785901543756                              |
| Nbr. of units in pkg. | 1   |
| Package weight(Lbs)   | 3.00 lb(US) (1.361 kg)                    |
| Returnability         | No  |
| Country of origin     | MX  |

## Packing Units

|                        |                       |
|------------------------|-----------------------|
| Unit Type of Package 1 | PCE                   |
| Package 1 Height       | 24.13 in (61.29 cm)   |
| Package 1 width        | 9.50 in (24.13 cm)    |
| Package 1 Length       | 61.29 in (155.677 cm) |

## Offer Sustainability

|                           |   |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation          | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive         | Not applicable, out of EU RoHS legal scope  |
| Environmental Disclosure  | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile       | <a href="#">End Of Life Information</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|