



Key-operated switch BKS, 22 mm, round, plastic, lock number S1, with 2 keys, 3 switch positions I>O<II, momentary contact on the left, latching on the right, actuating angle 2x45°, 10:30h/12h/13:30h, key removal O, with laser labeling, upper case and lower case, always upper case at beginning of line

|  |  |
|--|--|
| <b>product brand name</b>                              | SIRIUS ACT   |
| <b>product designation</b>                             | Key-operated switches  |
| <b>design of the product</b>                           | Actuating/signaling element  |
| <b>product type designation</b>                        | 3SU1   |
| <b>product line</b>                                    | Plastic, black, 22 mm  |
| <b>manufacturer's article number of included key</b>   | <a href="#">3SU1950-0FD80-0AA0</a>   |
| <b>Actuator</b>  |  |
| <b>principle of operation of the actuating element</b> | momentary contact/latching, 2x45° (10:30 h/12 h/13:30 h), return from left, right latching |
| <b>product extension optional light source</b>         | No   |
| <b>color</b>   |  |
| • of the actuating element                             | silver   |
| <b>material of the actuating element</b>               | metal  |
| <b>shape of the actuating element</b>                  | Key  |
| <b>outer diameter of the actuating element</b>         | 29.5 mm  |
| <b>marking of the actuating element</b>                | Any inscription, text in upper/lower case, every line begins with upper case letter        |
| <b>number of switching positions</b>                   | 3  |
| <b>switch position for key distraction</b>             | O  |
| <b>actuating angle</b>                                 |  |
| • clockwise  | 45°  |
| • anticlockwise  | 45°  |
| <b>lock make</b>                                       | BCS  |
| <b>key number</b>                                      | S1   |
| <b>Front ring</b>                                      |  |
| <b>product component front ring</b>                    | Yes  |
| <b>design of the front ring</b>                        | Standard   |
| <b>material of the front ring</b>                      | plastic  |
| <b>color of the front ring</b>                         | black  |
| <b>General technical data</b>                          |  |
| <b>protection class IP</b>                             | IP66, IP67, IP69(IP69K)  |
| • of the terminal                                      | IP20   |
| <b>degree of protection NEMA rating</b>                | 1, 2, 3, 3R, 4, 4X, 12, 13   |
| <b>shock resistance</b>                                |  |
| • according to IEC 60068-2-27                          | sinusoidal half-wave 15g / 11 ms   |
| • for railway applications according to EN 61373       | Category 1, Class B  |
| <b>vibration resistance</b>                            |  |
| • according to IEC 60068-2-6                           | 10 ... 500 Hz: 5g  |
| • for railway applications according to EN 61373       | Category 1, Class B  |
| <b>operating frequency maximum</b>                     | 1 800 1/h  |

|  |  |
|--|--|
| mechanical service life (switching cycles) typical             | 1 000 000  |
| reference code according to IEC 81346-2                        | S  |
| Substance Prohibitance (Date)                                  | 10/01/2014   |
| <b>Ambient conditions</b>                                      |  |
| <b>ambient temperature</b>                                     |  |
| • during operation   | -25 ... +70 °C   |
| • during storage   | -40 ... +80 °C   |
| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |
| <b>Installation/ mounting/ dimensions</b>                      |  |
| <b>height</b>  | 29.5 mm  |
| <b>width</b>   | 29.5 mm  |
| <b>shape of the installation opening</b>                       | round  |
| <b>mounting diameter</b>                                       | 22.3 mm  |
| <b>positive tolerance of installation diameter</b>             | 0.4 mm   |
| <b>mounting height</b>   | 56.3 mm  |
| <b>installation width</b>                                      | 29.5 mm  |
| <b>installation depth</b>                                      | 25.4 mm  |
| <b>Certificates/ approvals</b>                                 |  |
| <b>Further information</b>                                     |  |

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1000-5PP01-0AA0-Z Y10>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1000-5PP01-0AA0-Z Y10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1000-5PP01-0AA0-Z Y10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1000-5PP01-0AA0-Z Y10&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1000-5PP01-0AA0-Z Y10&lang=en)

last modified:

1/26/2022 