## **SIEMENS**

## **Data sheet**



Illuminated mushroom pushbutton, 22 mm, round, plastic, green, 40 mm, momentary contact type, Z=50-unit packaging

| product brand name   | SIRIUS ACT                       |
|--|----------------------------------|
| product designation  |                                  |
| product designation  | Mushroom pushbuttons             |
| design of the product  | Actuating/signaling element 3SU1 |
| product type designation   |                                  |
| product line   | Plastic, black, 22 mm            |
| Enclosure  |                                  |
| number of command points   | 1                                |
| Actuator   |                                  |
| design of the actuating element                                    | illuminated                      |
| principle of operation of the actuating element                    | momentary contact type           |
| product extension optional light source                            | Yes                              |
| color of the actuating element                                     | green                            |
| material of the actuating element                                  | plastic                          |
| shape of the actuating element                                     | round                            |
| outer diameter of the actuating element                            | 40 mm                            |
| number of switching positions                                      | 2                                |
| Front ring   |                                  |
| product component front ring                                       | Yes                              |
| design of the front ring   | Standard                         |
| material of the front ring   | plastic                          |
| color of the front ring  | black                            |
| General technical data   |                                  |
| product function   |                                  |
| <ul> <li>EMERGENCY OFF function</li> </ul>                         | No                               |
| EMERGENCY STOP function  | No                               |
| protection class IP  | IP66, IP67, IP69(IP69K)          |
| degree of protection NEMA rating                                   | 1, 2, 3, 3R, 4, 4X, 12, 13       |
| shock resistance   |                                  |
| <ul><li>according to IEC 60068-2-27</li></ul>                      | sinusoidal half-wave 15g / 11 ms |
| <ul> <li>for railway applications according to EN 61373</li> </ul> | Category 1, Class B              |
| vibration resistance   |                                  |
| <ul> <li>according to IEC 60068-2-6</li> </ul>                     | 10 500 Hz: 5g                    |
| <ul> <li>for railway applications according to EN 61373</li> </ul> | Category 1, Class B              |
| operating frequency maximum  | 3 600 1/h                        |
| mechanical service life (switching cycles) typical                 | 3 000 000                        |
| reference code according to IEC 81346-2                            | S                                |
| Substance Prohibitance (Date)                                      | 10/01/2014                       |
| Ambient conditions   |                                  |
| ambient temperature  |                                  |

| <ul><li>during operation</li></ul>                             | -25 +70 °C   |
|--|--|
| during storage   | -40 +80 °C   |
| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%) |
| Installation/ mounting/ dimensions                             |  |
| height   | 40 mm  |
| width  | 40 mm  |
| shape of the installation opening                              | round  |
| mounting diameter  | 22.3 mm  |
| positive tolerance of installation diameter                    | 0.4 mm   |
| mounting height  | 27.5 mm  |
| installation width   | 40 mm  |
| installation depth   | 24.4 mm  |
| Certificates/ approvals  |  |
| Further information  |  |

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-1BD40-0AA0-Z X90

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1001-1BD40-0AA0-Z X90

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-1BD40-0AA0-Z X90

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1001-1BD40-0AA0-Z X90&lang=en">http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1001-1BD40-0AA0-Z X90&lang=en</a>

1/27/2022 last modified: