



# Fox<sup>®</sup> Tie-On Cable Labels

A tough PVC tie-on cable label made from PVC.  
Ideal for commercial applications.

Print via Fox-in-a-Box<sup>®</sup> thermal printer using "One One One" as for all our range of thermal labels using the Basic / Advanced / Professional.

How many labels can be printed from one ribbon?

By way of example: LCP1-8015T (80mm x 15mm) will yield approx. 3,200 labels.

## TESTING

Test	Method
Resistance to Solvents	MIL-STD-202-215 w/change 1
Elevated Temperature	In House - 1000 hours @ 70C
Low Temperature	In House - 1000 hours @ -18C

## TECHNICAL DATA

Printing method:	DTP-1 Printer
Thermal Ribbon:	TSR3
Material:	PVC
Thickness:	1mm
Colours:	White/Yellow
RoHS:	Yes
Reach:	Yes



For more information and to discuss your needs please contact our sales team on: +44 (0)1707 37 37 27 or email [sales@silverfox.co.uk](mailto:sales@silverfox.co.uk) | [www.silverfox.co.uk](http://www.silverfox.co.uk) | [support@silverfox.co.uk](mailto:support@silverfox.co.uk)

Copyright © Silver Fox | 2020 Version 2



# Fox<sup>®</sup> Tie-On Cable Labels

## Additional Information

### FEATURES & BENEFITS

- Easy to use and apply
- Pre-perforated for rapid removal from roll
- Apply to any cable from OD Ø 10mm - unlimited
- Choice of two colours and eight sizes

## ORDER INFORMATION

Product Code	Label	Labels	Rolls	Labels per pack	Colours
	Dims (mm)	Per Roll	per Pack		
LCP1-6015T	60 x 15	150	5	750	○ ●
LCP1-8015T	80 x 15	140	5	700	○ ●
LCP1-10015T	100x15	120	5	600	○ ●
LCP1-12015T	120x15	100	5	500	○ ●
LCP1-6025T	60x25	150	3	450	○ ●
LCP1-8025T	80x25	140	3	420	○ ●
LCP1-10025T	100x25	120	3	360	○ ●
LCP1-12025T	120x25	100	3	300	○ ●



## STORAGE INSTRUCTIONS

Storage Instructions	Store between 50°F (10°C) and 77°F (25°C)
Conditions	Keep in dark conditions
Humidity Resistance	35% to 65% RH

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice. E&OE.



For more information and to discuss your needs please contact our sales team on: +44 (0)1707 37 37 27 or email [sales@silverfox.co.uk](mailto:sales@silverfox.co.uk) | [www.silverfox.co.uk](http://www.silverfox.co.uk) | [support@silverfox.co.uk](mailto:support@silverfox.co.uk)

Copyright © Silver Fox | 2020 Version 2