



eCon 3000

**Ethernet Switch**  
**Ha-VIS eCon 3061-AD**  
 7-port Ethernet Switch for vertical installation in control cabinets,  
 including 1 F.O. port (SC, MM)

Unmanaged	IP 30	PROFINET compatible <input checked="" type="checkbox"/>	EtherNet/IP compatible <input checked="" type="checkbox"/>
-----------	-------	---------------------------------------------------------	------------------------------------------------------------

Number of ports, Copper / Termination	6x 10/100Base-T(X) / RJ45 (Twisted Pair)
Number of ports, F.O. / Termination	1x 100Base-FX / SC-D female
Input voltage / Termination	24 V DC / 3-pole, pluggable screw contact (24 V, 0, FE)
Permissible range (min./max.)	9.6 V ... 60 V DC
Input current	approx. 200 mA (at 24 V DC)
Housing material	metal, powder-coated
Dimensions (W x H x D)	23 x 130 x 100 mm (without connectors)
Weight	approx. 0.6 kg
Working temperature	-10 °C ... +70 °C
Approvals	UL 508
MTBF	825.000 h

Identification	Part number	Drawing	Dimensions in mm
----------------	-------------	---------	------------------

Ha-VIS eCon 3061-AD  
 Ethernet Switch with  
 6 RJ45 ports  
 1 F.O. port

20 76 107 3100

