## **SIEMENS**

## **Data sheet**



Illuminated mushroom pushbutton, 22 mm, round, metal, shiny, amber, 60 mm, momentary contact type, with laser labeling, symbol number according to, ISO 7000 or IEC 60417

| product brand name                                 | SIRIUS ACT  |
|--|---|
| product designation                                | Mushroom pushbuttons  |
| design of the product                              | Actuating/signaling element   |
| product type designation                           | 3SU1  |
| product line                                       | Metal, shiny, 22 mm   |
| Enclosure  |   |
| number of command points                           | 1   |
| Actuator   |   |
| design of the actuating element                    | illuminated   |
| principle of operation of the actuating element    | momentary contact type  |
| product extension optional light source            | Yes   |
| color of the actuating element                     | amber   |
| material of the actuating element                  | plastic   |
| shape of the actuating element                     | round   |
| outer diameter of the actuating element            | 60 mm   |
| marking of the actuating element                   | Customized labeling, graphical symbols acc. to ISO7000 and IEC60417 |
| number of switching positions                      | 2   |
| Front ring   |   |
| product component front ring                       | Yes   |
| design of the front ring                           | Standard  |
| material of the front ring                         | Metal, high gloss   |
| color of the front ring                            | silver  |
| General technical data                             |   |
| product function                                   |   |
| <ul> <li>EMERGENCY OFF function</li> </ul>         | No  |
| EMERGENCY STOP function                            | No  |
| protection class IP                                | IP66, IP67, IP69(IP69K)   |
| degree of protection NEMA rating                   | 1, 2, 3, 3R, 4, 4X, 12, 13  |
| shock resistance                                   |   |
| according to IEC 60068-2-27                        | sinusoidal half-wave 15g / 11 ms                                    |
| vibration resistance                               |   |
| according to IEC 60068-2-6                         | 10 500 Hz: 5g   |
| operating frequency maximum                        | 3 600 1/h   |
| mechanical service life (switching cycles) typical | 3 000 000   |
| reference code according to IEC 81346-2            | S   |
| Substance Prohibitance (Date)                      | 10/01/2014  |
| Ambient conditions                                 |   |
| ambient temperature                                |   |
| <ul> <li>during operation</li> </ul>               | -25 +70 °C  |

| during storage   | -40 +80 °C   |
|--|--|
| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%) |
| Installation/ mounting/ dimensions                             |  |
| height   | 60 mm  |
| width  | 60 mm  |
| shape of the installation opening                              | round  |
| mounting diameter  | 22.3 mm  |
| positive tolerance of installation diameter                    | 0.4 mm   |
| mounting height  | 27.5 mm  |
| installation width   | 60 mm  |
| installation depth   | 24.4 mm  |
| Certificates/ approvals  |  |
| Further information  |  |

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1051-1CD00-0AA0-Z Y13

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1051-1CD00-0AA0-Z Y13

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1051-1CD00-0AA0-Z Y13

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1051-1CD00-0AA0-Z Y13&lanq=en

last modified: 1/27/2022 **C**