

GENERAL SPECIFICATIONS:

RATING: 2.5A / 250V AC

CABLE TYPE / SIZE: H03VVH2-F. 2 x 0.75 mm²

TEMPERATURE RATING: 75°C

CONDUCTOR COLORS: **BROWN / BLUE**

CABLE JACKET COLOR: **BLACK**

OVERALL LENGTH (L): 1800 + 50 mm

END 'A' PLUG: BS 546

END 'B': IEC-320 / C7


APPROVALS PLUG: SABS APPROVALS CABLE: **VDE**

APPROVALS CONNECTOR: VDE

PACKING:

HANKED

 $L = 180 \pm 25 \text{ mm}$



NOTES

В

NOTES:

1. PLUG MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).

DESCRIPTION

RELEASED

DASH

By pudxc at 1:24 pm, May 23, 2019

PART NO

REV



NOTES:

Contents of this document

prior notice

are subject to change without

1. CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).



Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL,CSA or EN Standards for proper installation instruction.

Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

NO.					
TABULATION BLOCK					
		TOLERA DECIMALS .xx +/- 0.1 .xxx +/005	ANCES: ANGULAR +/- 1°	GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111	
INIT.BY: E	DATE: 03/21/00	MILLIMETERS .xx +/- 0.3 .xxx +/013	ANGULAR +/- 1°	DWG TITLE: INTERNATIONAL DETACHABLE CORDS	ET
DRAWN: N	DATE: 03/21/00	FSCN No.: G, CC	SIZE A		REV. E
APRVD: DI	MR DATE: 03/21/00	SCALE: N	ONE	PART NO: 2084111M8703(R)	SHEET 1/1