

# Data sheet

## 2098.0 SI K 5x25 4,000A-F



Fuse, Dimensions: 5x25 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 250 V, Rated current: 4 A

### Business data

Article number	2098.0
Article name	SI K 5x25 4,000A-F
GTIN (EAN)	4044211049065
Indicator colour	Brown
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	1.22 g
Weight per piece (including packaging)	1.3 g
Unit of weight	G
Customs number	85361010
Country of origin	EU
Product description	fuse

### Technical data

#### Dimensions

Length	25 mm
Diameter of contact cap	5.2 mm
Optical defect display available	✓
Dimensions	5x25 mm

#### Ratings

Rated voltage	250 V
Rated current	4 A

#### Materials

Contact caps	Brass
Surface	Nickel
Tube	Ceramic

#### Further technical data

Trigger characteristic	Fast-acting (F)
Rated breaking capacity	1500 A @ AC 250 V
Voltage drop	200 mV
Power loss (@ 1.5 In)	1.7 W
Melting integral I <sup>2</sup> ts	16 A <sup>2</sup> s

#### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

---

**Media**

---

---

**Accessories**

---