

# Thermal Grease 21-430SF

Version TDS.21-430SF V.A.0

## Description

Thermal Grease 21-430SF is grease-like silicon-free thermal interface material, designed to perform low thermal resistance between high watt density chips like CPUs, GPUs, ASICs, Northbridge chipsets and heat sink. It provides outstanding reliability while remaining stable through all industry standard reliability testing.



## Benefits

- Moderate Viscosity
- Low Thermal Resistance
- High Thermal Conductivity
- RoHS Compliant
- Solvent-free


## Applications

- CPUs (Notebooks, PCs, Servers)
- LED Solid State Lighting
- GPUs
- Northbridge Chipsets
- ASICs Chips

## Typical Properties

Properties	21-430SF	Test Method
Thermal	Thermal Conductivity (W/m-k)	3
	Thermal Resistance @10 psi (in <sup>2</sup> °C/W)	0.030
	Thermal Resistance @50 psi (in <sup>2</sup> °C/W)	0.023
	Continuous Use Temp. (°C)	-40~150
Physical	Substrate	Silicone-free
	Color	Light Grey
	Viscosity (cPs)	300,000
Electrical	Specific Gravity (g/cc)	2.65
	Dielectric Strength (KVAC/mm)	>7
	Volume Resistivity (ohm-cm)	>10 <sup>14</sup>
	Dielectric Constant @1MHz	4.12
Regulatory	Flammability Rating	V0
	Shelf Life @25°C (Month)	6
	RoHS Compliant	YES

## Thermal Resistance vs. Compression



## Standard Package

Supplied in the package of 2 kg (1litre), 8kg (1 gallon) and 30 kg (5 gallon).

## Storage Requirement

Room Temperature under 25 °C  
\* Unopened Original Package

## Disclaimers

- The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the issuing date of this TDS. When using our products, no matter what type of equipment they might be used for, be sure to make a written agreement on the specifications with us in advance. The design and specifications in this TDS are subject to change without prior notice.
- Do not use the products beyond the specifications described in this TDS. This TDS explains the typical performance of the products as individual component. Before use, check and evaluate their operations when installed in your products.
- Install the following systems for a failsafe design to ensure safety if these products are to be used in equipment where a defect in these products may cause the loss of human life or other significant damage, such as damage to vehicles (automobile, train, vessel), traffic lights, medical equipment, aerospace equipment, electric heating appliances, combustion/gas equipment, rotating equipment, and disaster/crime prevention equipment.

