

1		2		3		4		5		6	
FEMALE END VIEW								SPECIFICATIONS			
1 2 10 3 11 4 5 6 12 7 8 9 9 SHIELD 1. BN 2. BU 3. WH 4. BN/RD 5. OG 6. YE 7. GY 8. PK 9. RD 10. BN/WH 11. BU/WH 12. GN/WH		HARTING P/N		Type of cable		Cable length(mm)		CONTANCT CARRIER MATERIAL/COLOR		PBT/WHITE	
		21373500C71050		PVC		5000 ⁺²⁰⁰ ₋₀		MOLDED HEAD MATERIAL/COLOR		TPU/BLACK	
		21373500C71100		PVC		10000 ⁺⁴⁰⁰ ₋₀		CONTACT MATERIAL/COLOR		BRASS/SILVER	
								COUPLING NUT MATERIAL/PLATING		ZINC ALLOY/NICKEL	
								RATED CURRENT		6 A	
								RATED VOLTAGE		300 V	
								OUTER CABLR JACKET MATERIAL/COLOR		PVC/BLACK	
								CONDUCTOR INSULATION MATERIAL		PVC	
								NUMBER OF CONDUCTORS (AWG)		12X18AWG	
								OPERATING TEMPERATURE		-40°C — +80°C	
								PROTECTION CLASS		IEC IP67	
		83.2 100±5 10±3 φ26 M23X1 SHIELD CONNECTED TO COUPLING *M									
All Dimensions in mm Tech. Character. Free size tol. According to production drawing All rights reserved Department HCS - CN HARTING Customised Solutions D-32339 Espelkamp Created by LINI Inspected by LIANL Standardisation LIANL Date 2022-10-13 State Final release Title M23_12P FE,Int-thread,STR PVC cable,xxM Doc-Key / ECM-Nr. / Type TB Number 2137 35 00 C 71 XXX Rev. A Page 1/1											