

Data sheet

2154.0 Q 0,5 m/82 Pole



Cross-connector, No. of poles: 82, Mounting type: Screwable, Width: 500 mm, Rated cross-section: 2.5 mm², Colour: natural

Business data

Article number	<u>2154.0</u>
Article name	Q 0,5 m/82 Pole
GTIN (EAN)	4044211049751
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	71.87 g
Weight per piece (including packaging)	73.6 g
Unit of weight	G
Customs number	85389099
Country of origin	CZ
Product description	Cross-connector
Colour	Natural

Technical data

Dimensions

Length	4 mm
Width	500 mm
Hole height	2.5 mm
Hole diameter	2.8 mm
Hole spacing (mid-point to mid-point)	6.1 mm
Pitch size	6 mm
Slotted hole	✓

Ratings

Voltage with partition, max.	400 V
Voltage without partition, max.	400 V
Rated current	20 A
Rated cross-section	2.5 mm ²
Contamination degree	3

Connection data

No. of poles	82
Screw head	Slotted
Screw threading	M 2,5
Tightening torque, min.	0.4 Nm
Tightening torque, max.	0.8 Nm

Materials

Material	Copper
Surface	Tin-plated
Surface screw	Galvanized

Further technical data

Mounting type	Screwable
---------------	-----------

Data sheet

2154.0 Q 0,5 m/82 Pole



Technical data

Environmental Product Compliance

REACH Conform	No
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
REACH CAS 1 Substance	LEAD
REACH CAS 1 Percent minimal	0.1 %
REACH CAS 1 Percent maximum	4 %
REACH CAS 1 Number	7439-92-1
RoHS Conform	yes
RoHS Exception rule	6c

Media



Data sheet

2154.0 Q 0,5 m/82 Pole

Accessories

Screwdriver

Screwdriver with bare blade, Colour: Black-grey



Article number	Article name	GTIN (EAN)	Packaging unit
<u>1086.0</u>	SDB 0,6x3,5	4044211014797	1 ST

##INVERSE##CONTA-CONNECT

Three-wire installation terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 6 mm, Colour: Beige



Article number	Article name	GTIN (EAN)	Packaging unit
<u>1416.2</u>	DLIS 2,5 L BG	4044211044619	50 ST

##INVERSE##CONTA-CONNECT


Three-wire installation terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 6 mm, Colour: Beige



Article number	Article name	GTIN (EAN)	Packaging unit
<u>1417.2</u>	DLI 2,5 PE/L/NT BG	4044211044626	50 ST

##INVERSE##CONTA-CONNECT

Three-wire installation terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 18 mm, Colour: Beige




Article number	Article name	GTIN (EAN)	Packaging unit
<u>2716.2</u>	DLIS 2,5 B-3L/N/PE BG	4044211129903	25 ST

##INVERSE##CONTA-CONNECT

Data sheet

2154.0 Q 0,5 m/82 Pole



Three-wire installation terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 18 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1448.2</u>	DLI 2,5 B-W BG	4044211044978	16 ST

##INVERSE##CONTA-CONNECT



Three-wire installation terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 6 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1420.2</u>	DLI 2,5 L/N BG	4044211044657	50 ST