

Data sheet

2215.0 H 16,0/28 GN



Wire-end ferrules, Max. wire cross-section: 16 mm², Length: 28 mm, Length of copper pipe: 18 mm, Colour: Green

Business data

| | |
|--|---------------|
| Article number | 2215.0 |
| Article name | H 16,0/28 GN |
| GTIN (EAN) | 4044211050382 |
| Packaging unit | 100 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 0.92 g |
| Weight per piece (including packaging) | 0.94 g |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | DE |
| Product description | Ferrules |
| Colour | Green |

Data sheet

2215.0 H 16,0/28 GN

Technical data

Dimensions

| | |
|----------------------------------|--------|
| Length | 28 mm |
| Length of copper pipe | 18 mm |
| Diameter of copper pipe | 5.8 mm |
| Diameter plastic collar | 8.8 mm |
| Wall thickness of copper pipe | 0.2 mm |
| Wall thickness of plastic collar | 0.4 mm |

Connection data

| | |
|------------------------------|--------------------|
| Wire cross-section, max. | 16 mm ² |
| Wire cross-section AWG, max. | 6 |
| Stripping length | 21 mm |

Materials

| | |
|---------------------------|--------------------------------|
| Copper pipe | Copper alloy |
| Surface | Galvanically tin-plated, shiny |
| Plastic collar | Polypropylene homopolymer |
| Working temperature, min. | -5 °C |
| Working temperature, max. | 105 °C |

Further technical data

| | |
|----------------------|---|
| Insulation available | ✓ |
|----------------------|---|

Environmental Product Compliance

| | |
|--------------------------------|------------|
| REACH Conform | yes |
| REACH Reference date | 2023-06-14 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

Data sheet

2215.0 H 16,0/28 GN



Approvals

Standards and regulations

| | |
|------------------|-----|
| DIN 46228-4:1990 | yes |
|------------------|-----|

Media

Accessories
