

Coaxial Cable Connector

16_SMB-50-2-40/111_N

Description

Right angle cable plug

Interface standards
IEC 60169-10_MIL-STD-348A/311_CECC 22130



Technical Data

Electrical Data	
Impedance	50 Ω
Interface frequency max.	4 GHz
Mechanical Data	
Centre contact	crimped
Outer contact	crimped
Weight	0.0042 kg
Environmental Data	
Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Crimp ferrule	Copper	Gold Plating (without Nickel underplating)

Related Documents

Outline drawing	DOU-00007164
Catalogue drawing	DOU-00006816
Assembly instruction	DOC-0000179157

Ordering Information

Single package	16_SMB-50-2-40/111_NE
Bulk 100 pcs package	16_SMB-50-2-40/111_NH

Additional Information

Suitable cables	RG_316_/U, ENVIROFLEX_316, RG_188_A/U, RG_174_/U
-----------------	--