


## Coaxial Cable Connector 11\_SMA-50-3-100/111\_N

### Description

Straight cable plug

Interface standards

SUHNER-SMA-26.5GHz



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	26.5 GHz

#### Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.0028 kg

#### Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Coupling nut	Bronze	Gold Plating (Nickel underplated)
Gasket	VMQ (Silicone rubber)	

### Related Documents

Catalogue drawing	DCA-00007238
Assembly instruction	DOC-0000181590

### Ordering Information

Bulk 100 pcs package	11_SMA-50-3-100/111_NH
Single package	11_SMA-50-3-100/111_NE

### Additional Information

Suitable cables	EZ_141_TP_M17, SUCOFORM_141, MULTIFLEX_141
-----------------	--