



*Position of the contact when mounting into the housing  
acc. to 23 MV - A002*

All dimensions are in mm; tolerances according to ISO 2768 m-H

**Documents**

Instruction for Removal of the Contacts 23 MV-A002

**Material and plating**

**Connector parts**

Center contact  
Outer contact  
Dielectric  
Substrate

**Material**

CuBe  
CuBe  
PTFE  
Al<sub>2</sub>O<sub>3</sub>

**Plating**

Gold, min. 0.8 µm, over nickel  
Gold, min. 0.8 µm, over nickel

**Technical Data Sheet****Rosenberger**

Mini-Coax

Termination  
Jack**23K15A-010E4****Electrical data**

Impedance	50 $\Omega$
Frequency range	DC to 10 GHz
Return loss	$\geq 26$ dB, DC to 4 GHz $\geq 18$ dB, 4 GHz to 10 GHz
Center contact resistance	$\leq 10$ m $\Omega$
Outer contact resistance	$\leq 3$ m $\Omega$
Power handling	0.25 W at 25 °C

**Mechanical data**

Mating cycles	$\geq 500$
Engaging and disengaging force	1 N to 4 N

**Environmental data**

Temperature range	-40°C to +85°C
Climatic class	IEC 60068-2-1 40/85/21 IEC 60068-2-2 IEC 60068-2-3
Mechanical shock	IEC 60068-2-27 50G halvesinus, 2 shocks/axis during 11 sec.
RoHS	compliant

**Tooling**

Extraction tool for Metral insert	11W108-K00
-----------------------------------	------------

**Packing**

Weight	0.24 g/pce
--------	------------

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Marcel Panicke	26.11.08	Markus Hantschel	28.09.20	d00	20-1885	Marion Striegler	29.09.20
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de						Tel. : +49 8684 18-0 Email : info@rosenberger.de	
							Page 2 / 2