SIEMENS

Data sheet



Pushbutton, 22 mm, round, plastic, yellow, Front ring, raised momentary contact type, with laser labeling, lower case $\,$

product brand name	SIRIUS ACT
product draine name product designation	Pushbuttons
design of the product	Actuating/signaling element
product type designation	3SU1
product type designation	Plastic, black, 22 mm
•	Flastic, black, 22 IIIII
Enclosure	1
number of command points	1
Actuator	
design of the actuating element	Flat button
principle of operation of the actuating element	momentary contact type
product extension optional	
light source	No
contact module	Yes
color of the actuating element	yellow
material of the actuating element	plastic
shape of the actuating element	round
outer diameter of the actuating element	29.5 mm
marking of the actuating element	Customized labeling, text in lower case letters
Front ring	
product component front ring	Yes
product component front ring design of the front ring	Yes high
design of the front ring	high
design of the front ring material of the front ring	high plastic
design of the front ring material of the front ring color of the front ring	high plastic
design of the front ring material of the front ring color of the front ring General technical data	high plastic black
design of the front ring material of the front ring color of the front ring General technical data protection class IP	high plastic black IP66, IP67, IP69(IP69K)
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating	high plastic black IP66, IP67, IP69(IP69K)
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance	high plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27	high plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373	high plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 vibration resistance	high plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance	high plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance	high plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance	high plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B 3 600 1/h
design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance	high plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B 3 600 1/h 10 000 000

 ambient temperature during storage 	-40 +80 °C
environmental category during operation acc. to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95 %)
Installation/ mounting/ dimensions	
height	29.5 mm
width	29.5 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	18.1 mm
installation width	29.5 mm
installation depth	24.3 mm
Certificates/ approvals	
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1000-0CB30-0AA0-Z Y12

Cax online generator

 $\underline{\text{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=3SU1000-0CB30-0AA0-Z\ Y12}$

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1000-0CB30-0AA0-Z Y12

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1000-0CB30-0AA0-Z Y12&lang=en

last modified: 12/21/2020 🖸