



Cross-connection rail, No. of poles: 2, Mounting type: Can be screwed on, Width: 9.1 mm, Rated cross-section: 2.5 mm², Colour: natural

Business data

| | |
|--|-----------------------|
| Article number | 2417.0 |
| Article name | QS 2 |
| GTIN (EAN) | 4044211051990 |
| Packaging unit | 100 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 0.19 g |
| Weight per piece (including packaging) | 0.2 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | DE |
| Product description | Cross-connection rail |
| Colour | Natural |

Technical data

Dimensions

| | |
|---------------------------------------|--------|
| Length | 4 mm |
| Width | 9.1 mm |
| Height | 1 mm |
| Hole height | 2.5 mm |
| Hole diameter | 2.8 mm |
| Hole spacing (mid-point to mid-point) | 5.1 mm |
| Pitch size | 5 mm |
| Slotted hole | ✓ |

Ratings

| | |
|---------------------|---------------------|
| Rated cross-section | 2.5 mm ² |
|---------------------|---------------------|

Connection data

| | |
|--------------|---|
| No. of poles | 2 |
|--------------|---|

Materials

| | |
|----------|------------|
| Material | Copper |
| Surface | Tin-plated |

Further technical data

| | |
|-----------------------------|-----------|
| Mounting type | Screwable |
| Number of bridged terminals | 2 |


Environmental Product Compliance

| | |
|--------------------------------|------------|
| REACH Conform | yes |
| REACH Reference date | 2023-06-14 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

Media


Accessories

##INVERSE##CONTA-CONNECT



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1271.2</u> | IK 2,5 PNP/DC/LED(RD)/48V BG | 4044211037512 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1260.2</u> | IK 2,5 BG | 4044211035228 | 100 ST |




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1263.2</u> | IK 2,5 PNP/DC/LED(GN)/24V BG | 4044211035860 | 100 ST |




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1274.2</u> | IK 2,5 PNP/DC/LED(GN)/60V BG | 4044211037628 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------------|---------------|----------------|
| <u>1275.2</u> | IK 2,5 PNP/AC/LED(RD)/220V BG | 4044211037734 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1280.2</u> | IK 2,5 NPN/DC/LED(GN)/60V BG | 4044211038373 | 100 ST |

##INVERSE##CONTA-CONNECT




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------------|---------------|----------------|
| <u>1282.2</u> | IK 2,5 NPN/AC/LED(GN)/220V BG | 4044211038663 | 100 ST |




Three-level initiator terminal | Multi-wire terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>2268.2</u> | IKD 2,5/Q BG | 4044211050771 | 50 |




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1264.2</u> | IK 2,5 NPN/DC/LED(RD)/24V BG | 4044211036072 | 100 ST |




Three-level initiator terminal | Multi-wire terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1295.2</u> | IKD 2,5/F BG | 4044211040093 | 50 |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1278.2</u> | IK 2,5 NPN/DC/LED(GN)/48V BG | 4044211038021 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------------|---------------|----------------|
| <u>1281.2</u> | IK 2,5 NPN/AC/LED(RD)/220V BG | 4044211038557 | 100 ST |

##INVERSE##CONTA-CONNECT




Three-level initiator terminal | Multi-wire terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1295.2</u> | IKD 2,5/F BG | 4044211040093 | 50 |




Three-level initiator terminal | Multi-wire terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>2269.2</u> | IKD 2,5/F/Q BG | 4044211050795 | 50 ST |




Three-level initiator terminal | Multi-wire terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1261.2</u> | IKD 2,5 BG | 4044211035433 | 50 |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1262.2</u> | IK 2,5 PNP/DC/LED(RD)/24V BG | 4044211035655 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1265.2</u> | IK 2,5 NPN/DC/LED(GN)/24V BG | 4044211036287 | 100 ST |

##INVERSE##CONTA-CONNECT




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1272.2</u> | IK 2,5 PNP/DC/LED(GN)/48V BG | 4044211037567 | 100 ST |




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1276.2</u> | IK 2,5 PNP/AC/LED(GN)220V BG | 4044211037840 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------------|---------------|----------------|
| <u>1279.2</u> | IK 2,5 NPN/DC/LED(RD)/ 60V BG | 4044211038168 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1273.2</u> | IK 2,5 PNP/DC/LED(RD)/60V BG | 4044211037574 | 100 ST |

##INVERSE##CONTA-CONNECT



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1262.2</u> | IK 2,5 PNP/DC/LED(RD)/24V BG | 4044211035655 | 100 ST |