



Cross-connector, No. of poles: 4, Mounting type: Can be screwed on, Width: 19.3 mm, Rated cross-section: 2.5 mm², Colour: natural

Business data

| | |
|--|-----------------|
| Article number | 2424.0 |
| Article name | Q 4 |
| GTIN (EAN) | 4044211052065 |
| Packaging unit | 20 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 3.3 g |
| Weight per piece (including packaging) | 3.36 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | CZ |
| Product description | Cross-connector |
| Colour | Natural |

Technical data

Dimensions

| | |
|---------------------------------------|---------|
| Length | 4 mm |
| Width | 19.3 mm |
| Hole height | 2.5 mm |
| Hole diameter | 2.8 mm |
| Hole spacing (mid-point to mid-point) | 5.1 mm |
| Pitch size | 5 mm |
| Slotted hole | ✓ |

Ratings

| | |
|---------------------------------|---------------------|
| Voltage with partition, max. | 400 V |
| Voltage without partition, max. | 400 V |
| Rated current | 20 A |
| Rated cross-section | 2.5 mm ² |
| Contamination degree | 3 |

Connection data

| | |
|-------------------------|---------|
| No. of poles | 4 |
| Screw head | Slotted |
| Screw threading | M 2,5 |
| Tightening torque, min. | 0.4 Nm |
| Tightening torque, max. | 0.8 Nm |

Materials

| | |
|---------------|------------|
| Material | Copper |
| Surface | Tin-plated |
| Surface screw | Galvanized |

Further technical data

| | |
|-----------------------------|-----------|
| Mounting type | Screwable |
| Number of bridged terminals | 4 |

Technical data

Environmental Product Compliance


| | |
|--------------------------------|------------|
| REACH Conform | No |
| REACH Reference date | 2023-06-14 |
| REACH Candidate Substance Note | No |
| REACH CAS 1 Substance | LEAD |
| REACH CAS 1 Percent minimal | 0.1 % |
| REACH CAS 1 Percent maximum | 4 % |
| REACH CAS 1 Number | 7439-92-1 |
| RoHS Conform | yes |
| RoHS Exception rule | 6c |

Media




Accessories

##INVERSE##CONTA-CONNECT



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1271.2</u> | IK 2,5 PNP/DC/LED(RD)/48V BG | 4044211037512 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1260.2</u> | IK 2,5 BG | 4044211035228 | 100 ST |




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1263.2</u> | IK 2,5 PNP/DC/LED(GN)/24V BG | 4044211035860 | 100 ST |




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1274.2</u> | IK 2,5 PNP/DC/LED(GN)/60V BG | 4044211037628 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------------|---------------|----------------|
| <u>1275.2</u> | IK 2,5 PNP/AC/LED(RD)/220V BG | 4044211037734 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1280.2</u> | IK 2,5 NPN/DC/LED(GN)/60V BG | 4044211038373 | 100 ST |

##INVERSE##CONTA-CONNECT




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------------|---------------|----------------|
| <u>1282.2</u> | IK 2,5 NPN/AC/LED(GN)/220V BG | 4044211038663 | 100 ST |




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1264.2</u> | IK 2,5 NPN/DC/LED(RD)/24V BG | 4044211036072 | 100 ST |




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1264.2</u> | IK 2,5 NPN/DC/LED(RD)/24V BG | 4044211036072 | 100 ST |




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1277.2</u> | IK 2,5 NPN/DC/LED(RD)/48V BG | 4044211037918 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1278.2</u> | IK 2,5 NPN/DC/LED(GN)/48V BG | 4044211038021 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------------|---------------|----------------|
| <u>1281.2</u> | IK 2,5 NPN/AC/LED(RD)/220V BG | 4044211038557 | 100 ST |

##INVERSE##CONTA-CONNECT




Three-level initiator terminal | Multi-wire terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1295.2</u> | IKD 2,5/F BG | 4044211040093 | 50 |



Three-level initiator terminal | Multi-wire terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>2269.2</u> | IKD 2,5/F/Q BG | 4044211050795 | 50 ST |




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1262.2</u> | IK 2,5 PNP/DC/LED(RD)/24V BG | 4044211035655 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1272.2</u> | IK 2,5 PNP/DC/LED(GN)/48V BG | 4044211037567 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1265.2</u> | IK 2,5 NPN/DC/LED(GN)/24V BG | 4044211036287 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1272.2</u> | IK 2,5 PNP/DC/LED(GN)/48V BG | 4044211037567 | 100 ST |

##INVERSE##CONTA-CONNECT




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1276.2</u> | IK 2,5 PNP/AC/LED(GN)220V BG | 4044211037840 | 100 ST |



Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------------|---------------|----------------|
| <u>1279.2</u> | IK 2,5 NPN/DC/LED(RD)/ 60V BG | 4044211038168 | 100 ST |




Three-level initiator terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------------------|---------------|----------------|
| <u>1273.2</u> | IK 2,5 PNP/DC/LED(RD)/60V BG | 4044211037574 | 100 ST |



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1030.2</u> | SRK 2,5 BG | 4044211006723 | 100 |



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------|---------------|----------------|
| <u>1035.2</u> | SRK 2,5/15 BG | 4044211007737 | 100 |