

Double-level terminal with electronic components, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 6 mm, Colour: Beige

Kaufmännische Daten

|  |   |
|--|---|
| Artikelnummer                              | 2437.2  |
| Artikelbezeichnung                         | RKD 4/LED3(GN)/24V DC BG                          |
| GTIN (EAN)                                 | 4044211052270                                     |
| Packaging unit                             | 100   |
| Quantity unit                              | PC  |
| Weight per piece (not including packaging) | 12.6 g  |
| Weight per piece (including packaging)     | 13.57 g   |
| Unit of weight                             | G   |
| Customs number                             | 85369010  |
| Country of origin                          | BG  |
| Product description                        | Double-level terminals with electronic components |
| Colour                                     | Beige   |

### Technische Daten

#### Dimensions

|                  |         |
|------------------|---------|
| Length           | 60.2 mm |
| Width            | 6 mm    |
| Height TS 35/7.5 | 61 mm   |
| Height TS 32     | 65.5 mm |

#### Ratings

|                       |                   |
|-----------------------|-------------------|
| Rated voltage         | 24 DC V           |
| Rated current         | 10 A              |
| Rated cross-section   | 4 mm <sup>2</sup> |
| Rated impulse voltage | 6 kV              |
| Overvoltage category  | III               |
| Contamination degree  | 3                 |

#### Connection data

|  |                     |
|--|---------------------|
| Connection principle                                     | Screw connection    |
| Connection position                                      | Lateral             |
| Number of terminals per level                            | 2                   |
| Number of levels   | 2                   |
| Wire cross-section single-core (rigid) / stranded, min.  | 0.2 mm <sup>2</sup> |
| Wire cross-section single core (rigid)/stranded, max.    | 4 mm <sup>2</sup>   |
| Wire cross-section stranded, min.                        | 0.2 mm <sup>2</sup> |
| Wire cross-section stranded, max.                        | 4 mm <sup>2</sup>   |
| Wire cross-section stranded with wire-end ferrules, min. | 0.2 mm <sup>2</sup> |
| Wire cross-section stranded with wire-end ferrules, max. | 4 mm <sup>2</sup>   |
| Wire cross-section AWG, min.                             | 22                  |
| Wire cross-section AWG, max.                             | 12                  |
| Stripping length   | 9 mm                |
| Screw head   | Slotted             |
| Screw threading  | M 3                 |
| Tightening torque, min.                                  | 0.5 Nm              |
| Tightening torque, max.                                  | 1 Nm                |

### Technische Daten

#### Materials

|                           |               |
|---------------------------|---------------|
| Insulation housing        | Polyamide 6.6 |
| Flammability class UL 94  | V-2           |
| Working temperature, min. | -40 °C        |
| Working temperature, max. | 105 °C        |

#### Further technical data

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| Mounting type                         | Mounting rail TS 35/7.5 and TS 32 |
| Gauge plug acc. to EN 60 947-1        | A4                                |
| Number of cross-connection channels   | 2                                 |
| End plate required                    | ✓                                 |
| Voltage illuminated display           | 24 DC V                           |
| Cross-current via illuminated display | 5 mA                              |
| Colour of lamp                        | Green                             |

#### Environmental Product Compliance

|                                |            |
|--------------------------------|------------|
| REACH Conform                  | yes        |
| REACH Reference date           | 2023-06-14 |
| REACH Candidate Substance Note | No         |
| RoHS Conform                   | yes        |

### Zulassungen

#### Standards and regulations

|              |                |
|--------------|----------------|
| EAC approval | TR ZU 004/2011 |
|--------------|----------------|

|                      |     |
|----------------------|-----|
| EAC approval granted | yes |
|----------------------|-----|

#### CSA approval

|              |              |
|--------------|--------------|
| CSA approval | C22.2 No 158 |
|--------------|--------------|

|                      |     |
|----------------------|-----|
| CSA approval granted | yes |
|----------------------|-----|

|                               |       |
|-------------------------------|-------|
| CSA Usegroup C: rated voltage | 300 V |
|-------------------------------|-------|

|                               |      |
|-------------------------------|------|
| CSA Usegroup C: rated current | 25 A |
|-------------------------------|------|

|                                  |    |
|----------------------------------|----|
| CSA wire cross-section AWG, min. | 22 |
|----------------------------------|----|

|                                  |    |
|----------------------------------|----|
| CSA wire cross-section AWG, max. | 12 |
|----------------------------------|----|

|                      |      |
|----------------------|------|
| CSA stripping length | 9 mm |
|----------------------|------|

|                  |      |
|------------------|------|
| CSA torque, max. | 1 Nm |
|------------------|------|

|                  |        |
|------------------|--------|
| CSA torque, min. | 0.5 Nm |
|------------------|--------|

#### KEMA KEUR approval

|                    |                   |
|--------------------|-------------------|
| KEMA KEUR approval | EN 60947-7-1:2009 |
|--------------------|-------------------|

|                            |     |
|----------------------------|-----|
| KEMA KEUR approval granted | yes |
|----------------------------|-----|

|                    |       |
|--------------------|-------|
| KEMA rated voltage | 500 V |
|--------------------|-------|

|                    |      |
|--------------------|------|
| KEMA rated current | 32 A |
|--------------------|------|

|                            |      |
|----------------------------|------|
| KEMA rated impulse voltage | 6 kV |
|----------------------------|------|

|   |                     |
|---|---------------------|
| KEMA wire cross-section single core (rigid), min. | 0.2 mm <sup>2</sup> |
|---|---------------------|

|   |                   |
|---|-------------------|
| KEMA wire cross-section single-core (rigid), max. | 4 mm <sup>2</sup> |
|---|-------------------|

|  |                     |
|--|---------------------|
| KEMA wire cross-section stranded, min. | 0.2 mm <sup>2</sup> |
|--|---------------------|

|  |                   |
|--|-------------------|
| KEMA wire cross-section stranded, max. | 4 mm <sup>2</sup> |
|--|-------------------|

### Zulassungen




#### UL Recognized

|   |         |
|---|---------|
| UL approval   | UL 1059 |
| UL Usegroup C: rated voltage                        | 300 V   |
| UL Usegroup C: rated current                        | 30 A    |
| UL wire cross-section single-core (rigid) AWG, min. | 22      |
| UL wire cross-section single-core (rigid) AWG, max. | 10      |
| UL wire cross-section stranded AWG, min.            | 22      |
| UL wire cross-section stranded AWG, max.            | 10      |
| UL torque   | 7 Lb In |
| UL wire material                                    | Cu      |
| UL factory wiring                                   | 1       |
| UL field wiring                                     | 1       |
| UL Recognized                                       | 1       |

#### German Lloyd approval

|                            |                    |
|----------------------------|--------------------|
| DNV GL Location Classes    | C                  |
| DNV GL approval granted    | 1                  |
| DNV GL rated cross-section | 4 mm <sup>2</sup>  |
| DNV GL rated current       | 34 A               |
| DNV GL rated voltage       | 500 V              |
| DNV GL test standard       | IEC 60947-7-1:2002 |

### Medien



### Zubehör

#### End plate



End plate, Width: 1.5 mm, Colour: Beige

| Artikelnummer | Artikelbezeichnung | GTIN (EAN)    | VPE |
|---------------|--------------------|---------------|-----|
| <u>2101.2</u> | AP 4 BG            | 4044211151652 | 20  |

#### Insulation plate



Insulation plate, Colour: Beige

| Artikelnummer | Artikelbezeichnung | GTIN (EAN)    | VPE    |
|---------------|--------------------|---------------|--------|
| <u>2566.2</u> | TRS 3 BG           | 4044211053567 | 100 ST |

#### Screwdriver



Screwdriver with bare blade, Colour: Black-grey

| Artikelnummer | Artikelbezeichnung | GTIN (EAN)    | VPE  |
|---------------|--------------------|---------------|------|
| <u>1086.0</u> | SDB 0,6x3,5        | 4044211014797 | 1 ST |

#### Quick marking



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 6 mm, Colour: White

| Artikelnummer | Artikelbezeichnung | GTIN (EAN)    | VPE    |
|---------------|--------------------|---------------|--------|
| <u>4702.7</u> | PMC SB 6/50 WH     | 4044211089986 | 500 ST |

#### Socket plug



Screwdriver with bare blade, Colour: Black-grey

| Artikelnummer | Artikelbezeichnung | GTIN (EAN)    | VPE  |
|---------------|--------------------|---------------|------|
| <u>1086.0</u> | SDB 0,6x3,5        | 4044211014797 | 1 ST |

Datenblatt

2437.2 RKD 4/LED3(GN)/24V DC BG



Test plug



Test plug, Colour: Red

| Artikelnummer | Artikelbezeichnung | GTIN (EAN)    | VPE   |
|---------------|--------------------|---------------|-------|
| <u>2007.0</u> | PS 2,3             | 4044211048105 | 20 ST |