



MATERIALS:

- OVERMOLD - PVC, BLACK
- CABLE - 2 CONDUCTOR, 28AWG, SPIRAL SHIELDED
BLACK PVC JACKET
- PLUG - BRASS, NICKEL PLATED

NOTES:

1. PRIMARY UNITS ARE METRIC (MM [INCH]).
2. THIS PRODUCT IS RoHS COMPLIANT.

PART NUMBER	DIMENSION "X"	
	METERS	INCHES
250HR079250X	2 METERS+50mm/-0	79.00+2.00/-0

CUSTOMER DRAWING

					★ STAR SYMBOL DENOTES CRITICAL DIMENSION	THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.					
					UNLESS OTHERWISE SPECIFIED	SIZE	WIDTH	MULT	LBS/M	TEMPER	
					1. ALL DIMENSIONS IN INCHES -TWO PLACE DECIMALS ±0.01 -THREE PLACE DECIMALS ±0.005 -ANGLES ±1° -ALL DIA. CONCENTRIC WITHIN 0.005 T.I.R.	FINISH			MATERIAL		
					2. FEATURES ON THE SAME CENTERLINE MUST BE ALIGNED WITHIN ±0.002	SPEc No.			SPEc No.		
					3. REMOVE ALL BURRS	FIRST USED ON		SCALE 3:2		Switchcraft®	
A	26298	03-25-08	AH	TJK		DATE DRAWN	BY	CHKD	APVD	SHEET 1 OF 1	
						03-04-08	AH	AH 03-04-08	BDS 03-04-08		
REV	ECO NUMBER	DATE	BY	APVD	DO NOT SCALE DRAWING	NAME			PART No.		REV
REVISIONS						CABLE ASSEMBLY			250HR__250X		A
						2.5mm 3 CONDUCTOR ST TO ST, RoHS					

