


28155.7 PVC-PTSA 40X30 K WH



Device and installation marker, Length: 30 mm, Width: 40 mm, Colour: White

RAL: 9010

Business data

Article number	28155.7
Article name	PVC-PTSA 40X30 K WH
GTIN (EAN)	4044211213060
Packaging unit	150
Quantity unit	PC
Number of markers per card	6 ST
Weight per piece (not including packaging)	2.15 g
Weight per piece (including packaging)	2.15 g
Unit of weight	G
Customs number	39199080
Country of origin	IT
Prio-Article	28155.6
Product description	Device and installation marker

# Data sheet

## 28155.7 PVC-PTSA 40X30 K WH



### Technical data

#### Dimensions

Length	30 mm
Width	40 mm
Hole diameter	22.5 mm

#### Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

#### Further technical data

Mounting	Unter Bedienelement
Software code	1000

#### Environmental Product Compliance

REACH Candidate Substance Note	No
--------------------------------	----

---

**Media**

---

### Accessories

#### Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

#### Inlays

##### Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST