

Data sheet

28158.7 PVC-PTSA 60X40 K WH



Device and installation marker, Length: 40 mm, Width: 60 mm, Colour: White

RAL: 9010

Business data

Article number	28158.7
Article name	PVC-PTSA 60X40 K WH
GTIN (EAN)	4044211213114
Packaging unit	40
Quantity unit	PC
Number of markers per card	4 ST
Weight per piece (not including packaging)	4.36 g
Weight per piece (including packaging)	4.36 g
Unit of weight	G
Customs number	39199080
Country of origin	IT
Product description	Device and installation marker
Colour	White

Technical data

Dimensions

Length	40 mm
Width	60 mm
Hole diameter	31 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

Further technical data

Mounting	Self-adhesive
Software code	1005

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

Inlays

Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST