

Data sheet

28166.6 PVC-TAA 8X12 K GR



Device and installation marker, Length: 12 mm, Width: 8 mm, Colour: grey

RAL: Ähnlich 7035

Business data

| | |
|--|--------------------------------|
| Article number | <u>28166.6</u> |
| Article name | PVC-TAA 8X12 K GR |
| GTIN (EAN) | 4044211213664 |
| Packaging unit | 960 |
| Quantity unit | PC |
| Number of markers per card | 96 ST |
| Weight per piece (not including packaging) | 0.19 g |
| Weight per piece (including packaging) | 0.19 g |
| Unit of weight | G |
| Customs number | 39199080 |
| Country of origin | IT |
| Prio-Article | 28166.7 |
| Product description | Device and installation marker |

28166.6 PVC-TAA 8X12 K GR

Technical data

Dimensions

| | |
|--------|-------|
| Length | 12 mm |
|--------|-------|

| | |
|-------|------|
| Width | 8 mm |
|-------|------|

Materials

| | |
|-----------------|-----|
| Marker material | PVC |
|-----------------|-----|

| | |
|--------------------------|-----|
| Flammability class UL 94 | V-0 |
|--------------------------|-----|

| | |
|---------------------------|--------|
| Working temperature, min. | -30 °C |
|---------------------------|--------|

| | |
|---------------------------|-------|
| Working temperature, max. | 60 °C |
|---------------------------|-------|

| | |
|------------------------------|-------|
| Processing temperature, min. | 10 °C |
|------------------------------|-------|

| | |
|------------------------------|-------|
| Processing temperature, max. | 40 °C |
|------------------------------|-------|

| | |
|---------------|---|
| Silicone-free | ✓ |
|---------------|---|

Further technical data

| | |
|----------|---------------|
| Mounting | Self-adhesive |
|----------|---------------|

| | |
|---------------|-----|
| Software code | 723 |
|---------------|-----|

Environmental Product Compliance

| | |
|---------------|-----|
| REACH Conform | Yes |
|---------------|-----|

| | |
|--------------------------------|----|
| REACH Candidate Substance Note | No |
|--------------------------------|----|

| | |
|--------------|-----|
| RoHS Conform | Yes |
|--------------|-----|

Media

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>28000.0</u> | TTPCard Set | 4044211207397 | 1 ST |

Inlays

Printer inlay

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------|---------------|----------------|
| <u>28041.0</u> | CCI-PC/PVC/PVCF | 4044211208097 | 1 ST |