

Data sheet

28168.7 PVC-TAA 8,5X30 K WH



Device and installation marker, Length: 30 mm, Width: 8.5 mm, Colour: White

RAL: 9010

Business data

Article number	28168.7
Article name	PVC-TAA 8,5X30 K WH
GTIN (EAN)	4044211213640
For manufacturer type	ABB SNK LH
Packaging unit	330
Quantity unit	PC
Number of markers per card	33 ST
Weight per piece (not including packaging)	0.56 g
Weight per piece (including packaging)	0.56 g
Unit of weight	G
Customs number	39199080
Country of origin	IT
Prio-Article	28168.7
Product description	Device and installation marker

28168.7 PVC-TAA 8,5X30 K WH

Technical data

Dimensions

Length	30 mm
Width	8.5 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

Further technical data

Mounting	Self-adhesive
Software code	720

Environmental Product Compliance

REACH Candidate Substance Note	No
--------------------------------	----

Media

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

Inlays

Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST