

Data sheet

28178.7 PVC-TAA 15X49 K WH



Device and installation marker, Length: 49 mm, Width: 15 mm, Colour: White

RAL: 9010

Business data

Article number	<u>28178.7</u>
Article name	PVC-TAA 15X49 K WH
GTIN (EAN)	4044211213299
Packaging unit	140
Quantity unit	PC
Number of markers per card	14 ST
Weight per piece (not including packaging)	1.3 g
Weight per piece (including packaging)	1.3 g
Unit of weight	G
Customs number	39199080
Country of origin	IT
Prio-Article	28178.7
Product description	Device and installation marker

Technical data

Dimensions

Length	49 mm
--------	-------

Width	15 mm
-------	-------

Materials

Marker material	PVC
-----------------	-----

Flammability class UL 94	V-0
--------------------------	-----

Working temperature, min.	-30 °C
---------------------------	--------

Working temperature, max.	60 °C
---------------------------	-------

Processing temperature, min.	10 °C
------------------------------	-------

Processing temperature, max.	40 °C
------------------------------	-------

Silicone-free	✓
---------------	---

Further technical data

Mounting	Self-adhesive
----------	---------------

Software code	967
---------------	-----

Environmental Product Compliance

REACH Candidate Substance Note	No
--------------------------------	----

Media

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

Inlays

Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST