

Data sheet

28182.7 PVC-TAA 17X44 K WH



Device and installation marker, Length: 44 mm, Width: 17 mm, Colour: White

RAL: 9010

Business data

| | |
|--|--------------------------------|
| Article number | 28182.7 |
| Article name | PVC-TAA 17X44 K WH |
| GTIN (EAN) | 4044211213411 |
| Packaging unit | 120 |
| Quantity unit | PC |
| Number of markers per card | 12 ST |
| Weight per piece (not including packaging) | 1.6 g |
| Weight per piece (including packaging) | 1.6 g |
| Unit of weight | G |
| Customs number | 39199080 |
| Country of origin | IT |
| Prio-Article | 28182.7 |
| Product description | Device and installation marker |

Technical data

Dimensions

| | |
|--------|-------|
| Length | 44 mm |
|--------|-------|

| | |
|-------|-------|
| Width | 17 mm |
|-------|-------|

Materials

| | |
|-----------------|-----|
| Marker material | PVC |
|-----------------|-----|

| | |
|--------------------------|-----|
| Flammability class UL 94 | V-0 |
|--------------------------|-----|

| | |
|---------------------------|--------|
| Working temperature, min. | -30 °C |
|---------------------------|--------|

| | |
|---------------------------|-------|
| Working temperature, max. | 60 °C |
|---------------------------|-------|

| | |
|------------------------------|-------|
| Processing temperature, min. | 10 °C |
|------------------------------|-------|

| | |
|------------------------------|-------|
| Processing temperature, max. | 40 °C |
|------------------------------|-------|

| | |
|---------------|---|
| Silicone-free | ✓ |
|---------------|---|

Further technical data

| | |
|----------|---------------|
| Mounting | Self-adhesive |
|----------|---------------|

| | |
|---------------|-----|
| Software code | 717 |
|---------------|-----|

Environmental Product Compliance

| | |
|--------------------------------|----|
| REACH Candidate Substance Note | No |
|--------------------------------|----|

Media

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>28000.0</u> | TTPCard Set | 4044211207397 | 1 ST |

Inlays

Printer inlay

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------|---------------|----------------|
| <u>28041.0</u> | CCI-PC/PVC/PVCF | 4044211208097 | 1 ST |