


Data sheet

28209.7 PVC-VRT-RH 75X120 WH



Device and installation marker, Length: 120 mm, Width: 75 mm, Colour: White

RAL: 9010

Business data

Article number	28209.7
Article name	PVC-VRT-RH 75X120 WH
GTIN (EAN)	4044211215163
Packaging unit	25
Quantity unit	PC
Number of markers per card	1 ST
Weight per piece (not including packaging)	13.44 g
Weight per piece (including packaging)	13.44 g
Unit of weight	G
Customs number	39204910
Country of origin	IT
Prio-Article	28209.7
Product description	Device and installation marker

28209.7 PVC-VRT-RH 75X120 WH

Technical data

Dimensions

Length	120 mm
Width	75 mm
Diameter of mounting hole	4 mm
Thickness	0.9 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

Further technical data

Software code	816
Number of bore holes	4 ST

Environmental Product Compliance

REACH Candidate Substance Note	No
--------------------------------	----

Media

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

Inlays

Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST