



Test adapter, Length: 37.3 mm, Pitch size: 6 mm, Colour: Beige

Business data

Article number	2822.0
Article name	TAD 6/1/S
GTIN (EAN)	4044211055486
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	10 g
Weight per piece (including packaging)	10.06 g
Unit of weight	G
Customs number	85369010
Country of origin	DE
Product description	Test adapter
Colour	Beige

Data sheet

2822.0 TAD 6/1/S

Technical data

Dimensions

Length	37.3 mm
--------	---------

Pitch size	6 mm
------------	------

Connection data

Wire cross-section stranded, min.	0.5 mm ²
-----------------------------------	---------------------

Wire cross-section stranded, max.	1 mm ²
-----------------------------------	-------------------

Stripping length	5 mm
------------------	------

Materials

Insulation housing	Polyamide 6.6
--------------------	---------------

Flammability class UL 94	V-2
--------------------------	-----

Working temperature, min.	-40 °C
---------------------------	--------

Working temperature, max.	105 °C
---------------------------	--------

Environmental Product Compliance

REACH Conform	yes
---------------	-----

REACH Reference date	2023-06-14
----------------------	------------

REACH Candidate Substance Note	No
--------------------------------	----

RoHS Conform	yes
--------------	-----

Media

Accessories


Quick marking



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 5 mm, Colour: White


Article number	Article name	GTIN (EAN)	Packaging unit
<u>4600.7</u>	PMC SB 5/50 WH	4044211088903	500 ST

##INVERSE##CONTA-CONNECT




Double-level terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 6 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1020.2</u>	RKD 4 BG	4044211004545	100




Double-level terminal with electronic components, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 6 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>2323.2</u>	RKD 4/D4 BG	4044211051099	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 6 mm, Colour: Beige


Article number	Article name	GTIN (EAN)	Packaging unit
<u>2319.2</u>	RKD 4/D0 BG	4044211051051	100 ST



Double-level terminal with electronic components, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 6 mm, Colour: Beige


Article number	Article name	GTIN (EAN)	Packaging unit
<u>2320.2</u>	RKD 4/D6 BG	4044211051068	100 ST

##INVERSE##CONTA-CONNECT




Double-level terminal with electronic components, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 6 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>2321.2</u>	RKD 4/D5 BG	4044211051075	100 ST




Double-level terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 6 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1020.2</u>	RKD 4 BG	4044211004545	100




Ex double-level terminal ATEX-certified, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 4 mm², Width: 5 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1429.2</u>	RKD 4 Ex BG	4044211044763	100



Double-level terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1128.2</u>	RKD 4/35 BG	4044211019648	100



Double-level terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1128.2</u>	RKD 4/35 BG	4044211019648	100