



Cable entry with membrane for unassembled cables, Mounting type: Rasten, Length: 147 mm, Width: 58 mm, IP66, Colour: Black

RAL: 9005

Kaufmännische Daten

|                                            |                |
|--------------------------------------------|----------------|
| Artikelnummer                              | 28652.4        |
| Artikelbezeichnung                         | KES-R 16/24 BK |
| GTIN (EAN)                                 | 4044211220235  |
| Packaging unit                             | 10             |
| Quantity unit                              | PC             |
| Weight per piece (not including packaging) | 106.3 g        |
| Weight per piece (including packaging)     | 113.3 g        |
| Unit of weight                             | G              |
| Customs number                             | 39259020       |
| Country of origin                          | DE             |
| Prio-Article                               | 28652.6        |
| Product description                        | Cable Entry    |

### Technische Daten

#### Dimensions

|                       |          |
|-----------------------|----------|
| Length                | 149.6 mm |
| Length of wall cutout | 112 mm   |
| Width                 | 58 mm    |
| Width of wall cutout  | 36 mm    |
| Installation height   | 14.5 mm  |

#### Materials

|                           |               |
|---------------------------|---------------|
| Material                  | Polyamide 6.6 |
| Glass-fibre reinforced    | ✓             |
| Flammability class UL 94  | V-0           |
| Working temperature, min. | -40 °C        |
| Working temperature, max. | 90 °C         |
| Sealing material          | TPE           |
| Halogen-free              | ✓             |
| Silicone-free             | ✓             |

#### Further technical data

|                                                    |         |
|----------------------------------------------------|---------|
| Mounting type                                      | Snap-on |
| Degree of protection for snap-in mounting          | IP54    |
| Sheet thickness min.                               | 1.5 mm  |
| Sheet thickness max.                               | 2 mm    |
| NEMA Type                                          | 1       |
| Number of wires                                    | 16      |
| Number of cables for cable diameters 3.2 - 5.5 mm  | 8       |
| Number of cables for cable diameters 5.0 - 8.5 mm  | 6       |
| Number of cables for cable diameters 9.5 - 14.5 mm | 2       |

Zulassungen

|                 |                 |
|-----------------|-----------------|
| cUL Recognized  |                 |
| cUL approval    | C22.2 No. 14-18 |
| cUL File Number | E489821         |
| cUL Recognized  | 1               |
| UL Recognized   |                 |
| UL approval     | UL 508A         |
| UL File Number  | E489821         |
| UL Recognized   | 1               |
| UL Type Rating  | 1               |

### Medien



**c** **RA**<sup>®</sup> **US**



Zubehör

EMC brackets



Shield-connection rail enabling mounting of shield connection clips directly on cable entry system KDS and KES, Mounting type: Screw, Length: 35,3 mm, Width: 140 mm, Height: 16 mm, Profile: 10x3 mm

| Artikelnummer  | Artikelbezeichnung | GTIN (EAN)    | VPE  |
|----------------|--------------------|---------------|------|
| <u>28626.0</u> | KDS-EMV-SAB 10/24  | 4044211219659 | 1 ST |

Sheet-metal puncher



Sheet metal puncher for rectangular openings, Dimensions opening: 112 x 36 mm, Maximum wall thickness: 2.0 mm for stainless steel sheet, Material: steel

| Artikelnummer  | Artikelbezeichnung | GTIN (EAN)    | VPE  |
|----------------|--------------------|---------------|------|
| <u>28752.0</u> | BL-VA KES          | 4044211221935 | 1 ST |



Sheet metal puncher for rectangular openings, Dimensions opening: 112 x 36 mm, Maximum wall thickness: 2.0 mm for S 235 sheet, Material: steel

| Artikelnummer  | Artikelbezeichnung | GTIN (EAN)    | VPE  |
|----------------|--------------------|---------------|------|
| <u>28744.0</u> | BL KES             | 4044211221942 | 1 ST |