SIEMENS

Data sheet



Mushroom pushbutton, 22 mm, round, metal, shiny, black, 40 mm, momentary contact type, with laser labeling, upper case and lower case, always upper case at beginning of line

product designation design of the product product type designation product line Enclosure number of command points Actuating principle of operation of the actuating element product extension optional light source Mushroom pushbuttons Actuating/signaling element Metal, shiny, 22 mm 1 Actuator principle of operation of the actuating element product extension optional light source No		
product type designation product line Metal, shiny, 22 mm Enclosure number of command points 1 Actuator principle of operation of the actuating element product extension optional light source No		
product line Metal, shiny, 22 mm Enclosure number of command points 1 Actuator principle of operation of the actuating element momentary contact type product extension optional light source No		
Enclosure number of command points Actuator principle of operation of the actuating element product extension optional light source No		
number of command points Actuator principle of operation of the actuating element momentary contact type product extension optional light source No		
Actuator principle of operation of the actuating element momentary contact type product extension optional light source No		
principle of operation of the actuating element momentary contact type product extension optional light source No		
product extension optional light source No		
color of the naturating element		
color of the actuating element black		
material of the actuating element plastic		
shape of the actuating element round		
outer diameter of the actuating element 40 mm		
marking of the actuating element Customized labeling, text in lower case / capital letters, all lines with capital letter	start	
number of switching positions 2		
Front ring		
product component front ring Yes		
design of the front ring Standard		
material of the front ring Metal, high gloss		
color of the front ring silver		
General technical data		
product function		
EMERGENCY OFF function No		
EMERGENCY STOP function No		
protection class IP IP66, IP67, IP69(IP69K)		
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13		
shock resistance		
according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms		
vibration resistance		
• according to IEC 60068-2-6 10 500 Hz: 5g		
operating frequency maximum 3 600 1/h		
mechanical service life (switching cycles) typical 10 000 000		
reference code according to IEC 81346-2		
Substance Prohibitance (Date) 10/01/2014		
Ambient conditions		
ambient temperature		

during storage	-40 +80 °C	
environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)	
Installation/ mounting/ dimensions		
height	40 mm	
width	40 mm	
shape of the installation opening	round	
mounting diameter	22.3 mm	
positive tolerance of installation diameter	0.4 mm	
mounting height	27.5 mm	
installation width	40 mm	
installation depth	24.4 mm	
Certificates/ approvals		
Further information		

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-1BD10-0AA0-Z Y10

Cax online generator

 $\underline{\text{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=3SU1050-1BD10-0AA0-Z\ Y10-0AA0-Z\ Y10-0AA0-Z$

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-1BD10-0AA0-Z Y10

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1050-1BD10-0AA0-Z Y10&lang=en

last modified: 1/27/2022 **C**