

# Data sheet

## 2919.0 SI 5x20 0,160A-T



Fuse, Dimensions: 5x20 mm, Trigger characteristic: Slow-acting (T); Rated voltage: 250 V, Rated current: 0.16 A

### Business data

Article number	2919.0
Article name	SI 5x20 0,160A-T
GTIN (EAN)	4044211056445
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	0.86 g
Weight per piece (including packaging)	0.9 g
Unit of weight	G
Customs number	85361010
Country of origin	EU
Product description	fuse

### Technical data

#### Dimensions

Length	20 mm
Diameter of contact cap	5.2 mm
Dimensions	5x20 mm

#### Ratings

Rated voltage	250 V
Rated current	0.16 A

#### Materials

Contact caps	Brass
Surface	Nickel
Tube	Glass

#### Further technical data

Trigger characteristic	Time-lag (T)
Rated breaking capacity	35 A @ AC 250 V
Voltage drop	600 mV
Power loss (@ 1.5 I <sub>n</sub> )	0.3 W
Melting integral I <sup>2</sup> t <sub>s</sub>	0.4 A <sup>2</sup> s

#### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

---

### Approvals

---

#### Standards and regulations

---

Standards / specifications	IEC 60127-2/3 EN 60127-2/3 VDE 0820-2/3
----------------------------	---

---

---

**Media**

---

---

**Accessories**

---