



Fuse, Dimensions: 5x20 mm, Trigger characteristic: Slow-acting (T); Rated voltage: 250 V, Rated current: 0.63 A

Business data

|                                            |                  |
|--------------------------------------------|------------------|
| Article number                             | 2925.0           |
| Article name                               | SI 5x20 0,630A-T |
| GTIN (EAN)                                 | 4044211056506    |
| Packaging unit                             | 10               |
| Quantity unit                              | PC               |
| Weight per piece (not including packaging) | 0.96 g           |
| Weight per piece (including packaging)     | 1 g              |
| Unit of weight                             | G                |
| Customs number                             | 85361010         |
| Country of origin                          | EU               |
| Product description                        | fuse             |

### Technical data

#### Dimensions

|                         |         |
|-------------------------|---------|
| Length                  | 20 mm   |
| Diameter of contact cap | 5.2 mm  |
| Dimensions              | 5x20 mm |

#### Ratings

|               |        |
|---------------|--------|
| Rated voltage | 250 V  |
| Rated current | 0.63 A |

#### Materials

|              |        |
|--------------|--------|
| Contact caps | Brass  |
| Surface      | Nickel |
| Tube         | Glass  |

#### Further technical data

|                                                |                      |
|------------------------------------------------|----------------------|
| Trigger characteristic                         | Time-lag (T)         |
| Rated breaking capacity                        | 35 A @ AC 250 V      |
| Voltage drop                                   | 110 mV               |
| Power loss (@ 1.5 I <sub>n</sub> )             | 0.2 W                |
| Melting integral I <sup>2</sup> t <sub>s</sub> | 1.4 A <sup>2</sup> s |

#### Environmental Product Compliance

|                                |            |
|--------------------------------|------------|
| REACH Conform                  | yes        |
| REACH Reference date           | 2023-06-14 |
| REACH Candidate Substance Note | No         |
| RoHS Conform                   | yes        |

---

### Approvals

---

#### Standards and regulations

---

|                            |                                         |
|----------------------------|-----------------------------------------|
| Standards / specifications | IEC 60127-2/3 EN 60127-2/3 VDE 0820-2/3 |
|----------------------------|-----------------------------------------|

---

---

### Media

---

---

**Accessories**

---