

Data sheet

2935.0 SI 5x20 6,300A-T



Fuse, Dimensions: 5x20 mm, Trigger characteristic: Slow-acting (T); Rated voltage: 250 V, Rated current: 6.3 A

Business data

| | |
|--|------------------|
| Article number | 2935.0 |
| Article name | SI 5x20 6,300A-T |
| GTIN (EAN) | 4044211056605 |
| Packaging unit | 10 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 0.86 g |
| Weight per piece (including packaging) | 0.9 g |
| Unit of weight | G |
| Customs number | 85361010 |
| Country of origin | DE |
| Product description | fuse |

Technical data

Dimensions

| | |
|-------------------------|---------|
| Length | 20 mm |
| Diameter of contact cap | 5.2 mm |
| Dimensions | 5x20 mm |

Ratings

| | |
|---------------|-------|
| Rated voltage | 250 V |
| Rated current | 6.3 A |

Materials

| | |
|--------------|--------|
| Contact caps | Brass |
| Surface | Nickel |
| Tube | Glass |

Further technical data

| | |
|------------------------------------|----------------------|
| Trigger characteristic | Time-lag (T) |
| Rated breaking capacity | 63 A @ AC 250 V |
| Voltage drop | 70 mV |
| Power loss (@ 1.5 In) | 1.3 W |
| Melting integral I ² ts | 230 A ² s |

Environmental Product Compliance

| | |
|--------------------------------|------------|
| REACH Conform | yes |
| REACH Reference date | 2023-06-14 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

Approvals

Standards and regulations

| | |
|----------------------------|---|
| Standards / specifications | IEC 60127-2/3 EN 60127-2/3 VDE 0820-2/3 |
|----------------------------|---|

Media

Accessories
