

NSYTVR15

Vertical uprights height 1500mm. zinc-coated steel. Supply: 2 standard uprights.



Main

Range	Thalassa
Accessory / separate part category	Mounting accessory
Product or Component Type	Technical upright
Anwendung	Multi-purpose
Nennmaße des Gehäuses	59.06 in (1500 mm)
Mounting Support	Step slide Direct fixing on the rear inserts
Range compatibility	Thalassa PLA
Device composition	2 upright
Material	steel

Complementary

Surface Finish	Zinc coated
Fixing mode	Bosses inserts M8 - rear of enclosure
Adjustment	Adjustable in depth every 25 mm with caged nuts Adjustable in height every 2.5 mm with quarter-turn nuts
Height	Nominal 59.06 in (1500 mm) Real 54.13 in (1375 mm)
Width	1.77 in (45 mm)
Depth	1.34 in (34 mm)
Thickness	0.08 in (2 mm)
Cut-out dimensions	11 x 13 mm

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480185076
Nbr. of units in pkg.	1
Package weight(Lbs)	8.82 lb(US) (4.0 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.57 in (4 cm)
Package 1 width	2.36 in (6 cm)
Package 1 Length	54.13 in (137.5 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------