

Product: <u>9397</u> ☑





Product Description

24 AWG stranded (105x44) high-conductivity bare copper conductors, PVC insulation, double bare copper spiral shield (95% coverage), PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

	Conductor							
AWG	Stranding		Material			Nominal Diam	eter	No. of Conductors
24	105x44	BC -	Bare Copper (Hig	gh C	onductivity)	0.024 in		2
Condu	ictor Count:				2			
nsulat	ion							
	Material		Nominal Diameter Nominal V		Nominal V	Vall Thickness		
PVC - Polyvinyl Chloride 0.048 in		_	0.012 in					
PVC -	Polyvinyi Cni	oride	0.048 in		0.012 in			
Outer S		oride	0.048 in		0.012 in			
		oride	0.048 in	Со	0.012 in]		
Outer S	Shield Type				verage [%]]		
Outer S	Shield Type Serve / Scree		Material		verage [%]			
Outer S	Shield Type Serve / Scree		Material	959	verage [%] %			

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance
24.6 Ohm/1000ft	24.6 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield		
47.3 pF/ft	110 pF/ft		

Inductance

Nominal Inductance

Impedance

Nominal Characteristic Impedance
47 Ohm

Current

Max. Recommended Current [A] 3.36 Amps per Conductor at 25°C

Voltage



Temperature Range

Non-UL Temp Rating:	80°C
Operating Temperature Range:	-20°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	22 lbs/1000ft
Max. Pull Tension:	10 lbs
Min. Bend Radius/Minor Axis:	1.75 in

Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	No

Related Part Numbers

Variants

Item #	Color	Put-Up Type	Length	UPC			
9397 B59500	Black, Matte	Reel	500 ft	612825239949			
9397 B591000	Black, Matte	Reel	1,000 ft	612825239932			
Footnote:	Footnote:						

History

Update and Revision:	Revision Number: 0.379 Revision Date: 12-20-2022

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.