



Selector switch, illuminable, 30 mm, round, Metal, matte, white, selector switch, long, front ring for flush installation, 3 switch positions I>O<II, momentary contact type, actuating angle 2x45°, 10:30h/12h/13:30h, with laser labeling, upper case and lower case, always upper case at the beginning of the word

|  |   |
|--|---|
| product brand name                                 | SIRIUS ACT  |
| product designation                                | Selector switches   |
| design of the product                              | Actuating/signaling element   |
| product type designation                           | 3SU1  |
| product line                                       | Metal, matt, flat, 30 mm  |
| <b>Enclosure</b>                                   |   |
| number of command points                           | 1   |
| <b>Actuator</b>                                    |   |
| design of the actuating element                    | selector, long  |
| principle of operation of the actuating element    | momentary contact, 2x45° (10:30 h/12 h/13:30 h), return on both sides                           |
| product extension optional                         |   |
| • light source                                     | Yes   |
| • contact module                                   | Yes   |
| color of the actuating element                     | white   |
| material of the actuating element                  | plastic   |
| shape of the actuating element                     | Handle  |
| outer diameter of the actuating element            | 44.8 mm   |
| marking of the actuating element                   | Customized labeling, text in lower case / capital letters, all words start with capital letters |
| number of switching positions                      | 3   |
| actuating angle                                    |   |
| • clockwise  | 45°   |
| • anticlockwise                                    | 45°   |
| <b>Front ring</b>                                  |   |
| product component front ring                       | Yes   |
| design of the front ring                           | Flat  |
| material of the front ring                         | Metal, matt   |
| color of the front ring                            | sand gray   |
| <b>General technical data</b>                      |   |
| protection class IP                                | IP66, IP67, IP69(IP69K)   |
| degree of protection NEMA rating                   | 1, 2, 3, 3R, 4, 4X, 12, 13  |
| shock resistance                                   |   |
| • according to IEC 60068-2-27                      | sinusoidal half-wave 15g / 11 ms  |
| • for railway applications according to EN 61373   | Category 1, Class B   |
| vibration resistance                               |   |
| • according to IEC 60068-2-6                       | 10 ... 500 Hz: 5g   |
| • for railway applications according to EN 61373   | Category 1, Class B   |
| operating frequency maximum                        | 1 800 1/h   |
| mechanical service life (switching cycles) typical | 300 000   |

|  |  |
|--|--|
| reference code according to IEC 81346-2                        | S  |
| Substance Prohibitance (Date)                                  | 10/01/2014   |
| <b>Safety related data</b>                                     |  |
| B10 value with high demand rate according to SN 31920          | 300 000  |
| <b>proportion of dangerous failures</b>                        |  |
| • with low demand rate according to SN 31920                   | 20 %   |
| • with high demand rate according to SN 31920                  | 20 %   |
| failure rate [FIT] with low demand rate according to SN 31920  | 100 FIT  |
| <b>Ambient conditions</b>                                      |  |
| <b>ambient temperature</b>                                     |  |
| • during operation   | -25 ... +70 °C   |
| • during storage   | -40 ... +80 °C   |
| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |
| <b>Installation/ mounting/ dimensions</b>                      |  |
| height   | 44.8 mm  |
| width  | 44.8 mm  |
| shape of the installation opening                              | round  |
| mounting diameter  | 30.5 mm  |
| positive tolerance of installation diameter                    | 0.5 mm   |
| mounting height  | 22.1 mm  |
| installation width   | 44.8 mm  |
| installation depth   | 32.1 mm  |
| <b>Certificates/ approvals</b>                                 |  |
| <b>Further information</b>                                     |  |

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1062-2EM60-0AA0-Z Y15>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1062-2EM60-0AA0-Z Y15>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1062-2EM60-0AA0-Z Y15>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1062-2EM60-0AA0-Z Y15&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1062-2EM60-0AA0-Z Y15&lang=en)

last modified:

1/26/2022 