8501RS34V14

Plug in relay, Type R, hermetically sealed miniature, 5A resistive at 240 VAC, 14 blade, 4PDT, 4 NO, 4 NC, 24 VAC coil



Main

Product range	8501R	
Product type	Miniature Relay	
Relay Type	Low voltage	

Complementary

Mounting type	Socket	
Contact composition	4PDT	
[Uc] control circuit voltage	24 V AC	
Pilot light	No indicator	
Manual operator	Without test button	
Horsepower rating	Not rated	
Breaking capacity	5 A 120 V AC resistive control circuit UL 508 5 A 240 V AC resistive control circuit UL 508 5 A 30 V DC resistive control circuit UL 508	
Maximum switching voltage	30 V DC 240 V AC	
Contact material	Hermetically sealed silver tin oxide	
Operating time	20 ms - pick-up 20 ms - drop-out	
Shape of pins	Spade	
For use with	8501NR45	
Height	1.16 in (29.4 mm)	
Width	0.91 in (23.1 mm)	
Depth	1.53 in (38.9 mm)	

Environment

Ambient temperature range - operational	-40131 °F (-4055 °C)
Product certifications	UL Listed UL Recognized CSA CE

Ordering and shipping details

21143 - 8501 R	
CP2	
785901031871	
1	
1.92 oz (54.431 g)	
No	
CN	
	CP2 785901031871 1 1.92 oz (54.431 g) No

Pac	kin	a L	Inits

Unit Type of Package 1	PCE
Package 1 Height	2.10 in (5.334 cm)
Package 1 width	1.50 in (3.81 cm)
Package 1 Length	1.50 in (3.81 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☐ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Contraction Warranty	
Warranty	18 months