SIEMENS

Data sheet

3SU1031-0AD20-0AA0-Z Y11



Indicator light in illuminated pushbutton design, 22 mm, round, plastic with metal front ring, red, with laser labeling, upper case

| product brand name | SIRIUS ACT |
|--|--|
| product designation | Indicator lights |
| design of the product | Actuating/signaling element |
| product type designation | 3SU1 |
| product line | Plastic with metal front ring, matt, 22 mm |
| Enclosure | |
| number of command points | 1 |
| Actuator | |
| design of the actuating element | Illuminated pushbutton design |
| principle of operation of the actuating element | Fixed key |
| product extension optional | |
| light source | Yes |
| contact module | Yes |
| color of the actuating element | red |
| material of the actuating element | plastic |
| shape of the actuating element | round |
| outer diameter of the actuating element | 29.5 mm |
| marking of the actuating element | Any inscription, text in upper case |
| Front ring | |
| product component front ring | Yes |
| design of the front ring | Standard |
| material of the front ring | Metal, matt |
| color of the front ring | sand gray |
| General technical data | |
| protection class IP | IP66, IP67, IP69(IP69K) |
| degree of protection NEMA rating | 1, 2, 3, 3R, 4, 4X, 12, 13 |
| shock resistance | |
| according to IEC 60068-2-27 | sinusoidal half-wave 15g / 11 ms |
| for railway applications according to EN 61373 | Category 1, Class B |
| vibration resistance | |
| according to IEC 60068-2-6 | 10 500 Hz: 5g |
| for railway applications according to EN 61373 | Category 1, Class B |
| reference code according to IEC 81346-2 | S |
| Substance Prohibitance (Date) | 10/01/2014 |
| Ambient conditions | |
| ambient temperature | |
| during operation | -25 +70 °C |
| during storage | -40 +80 °C |
| environmental category during operation according to IEC | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%) |

| 60721 | | |
|---|---------|--|
| Installation/ mounting/ dimensions | | |
| height | 29.5 mm | |
| width | 29.5 mm | |
| shape of the installation opening | round | |
| mounting diameter | 22.3 mm | |
| positive tolerance of installation diameter | 0.4 mm | |
| mounting height | 11 mm | |
| installation width | 29.5 mm | |
| installation depth | 24.3 mm | |
| Certificates/ approvals | | |
| Eurthan information | | |

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1031-0AD20-0AA0-Z Y11

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1031-0AD20-0AA0-Z Y11

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1031-0AD20-0AA0-Z Y11

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <u>http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1031-0AD20-0AA0-Z_Y11&lang=en</u>

last modified:

1/26/2022 🖸