



NOTE: ALL DIMS ARE IN mm

MATERIAL:
 HOUSING: PBT POLYESTER UL94V-0
 MIXED GLASS FIBER
 STANDARD COLOR-BLACK
 CONTACTS: 0.35mm THICK PHOS-BRONZE
 PLATED WITH HARD GOLD AND
 GOLD FLASH IN SOLDER AREA
 .MATEL SHIELD-0.25mm THICK COPPER ALLOY
 PLATED WITH NICKEL
 CAVITY CONFIRMS TO FCC RULES AND
 REGULATIONS PART 68, SUBPART F.

- RDI PN: 3032S - X - X - XX - X - NL
 (A) 1 2 3 4 5 6
- 1- SERIES
 - 2- # OF JACKS (2-4)
 - 3- NUMBER OF POSITIONS (8)
 - 4- NUMBER OF CONTACTS (2,4,6,8)
 - 5- PLATING: 1 = 6u" Gold, 2 = 15u" Gold
 3 = 30u" Gold, 4 = 50u" Gold
 - 6- NL = ROHS COMPLIANT

PROJECTION	
SCALE	N/A
TOLERANCE	EXCEPT AS NOTED
DEC. MILLIMETERS	0.01±0.25 0.00±0.13 0.000±0.05
TITLE	RJ45 GANGED JACK/FULLY SHIELDED W/GROUNDING TABS-ROHS COMPLIANT (A)
DR.	Jlh
DATE	04/07/08
REF.	P/N:3032S-X-X-XX-X-NL
PRE-CK.	GM
DRAWING NO.	3415
SIZE	A
REV.	1 OF 1
SHEET	1

THIS DOCUMENT IS OWNED BY, AND THE INFORMATION CONTAINED IN IT IS PROPRIETARY TO, RDI. BY RECEIPT HEREOF THE HOLDER AGREES NOT TO USE THE INFORMATION AND NOT TO DISCLOSE IT TO ANY THIRD PARTY. NO REPRODUCTION OF THIS DOCUMENT WITHOUT THE WRITTEN CONSENT OF RDI. AND AGREES TO RETURN THIS DOCUMENT UPON REQUEST.

16-072	18/09/16	A	REVISION THE RDI P/N	Vicky Tho	ANG.	40°-30'
ECN#	DATE	SYM	REVISION RECORD	AUTH BY		