


Data sheet

3201.5 FRK 1,5/3A BU



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 1.5 mm², Width: 4.1 mm, Colour: Blue

RAL: Ähnlich 5005

Business data

| | |
|--|-----------------------|
| Article number | 3201.5 |
| Article name | FRK 1,5/3A BU |
| GTIN (EAN) | 4044211109639 |
| Packaging unit | 100 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 8 g |
| Weight per piece (including packaging) | 8.5 g |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | BG |
| Prio-Article | 3201.2 |
| Product description | Feed-through terminal |

Technical data

Dimensions

| | |
|------------------|---------|
| Length | 59.5 mm |
| Width | 4.1 mm |
| Height | 42.3 mm |
| Height TS 35/7.5 | 43 mm |

Ratings

| | |
|---|---------------------|
| Rated voltage | 800 V |
| Rated current | 17.5 A |
| Rated cross-section | 1.5 mm ² |
| Rated impulse voltage | 8 kV |
| Overvoltage category | III |
| Contamination degree | 3 |
| Maximum power dissipation for nominal condition | 0.56 W |

Connection data

| | |
|--|---------------------|
| Connection principle | Push-in connection |
| Connection position | Top |
| Connections | 3 |
| Number of terminals per level | 3 |
| Number of levels | 1 |
| Wire cross-section single-core (rigid) / stranded, min. | 0.2 mm ² |
| Wire cross-section single core (rigid)/stranded, max. | 1.5 mm ² |
| Wire cross-section stranded, min. | 0.2 mm ² |
| Wire cross-section stranded, max. | 1.5 mm ² |
| Wire cross-section stranded with wire-end ferrules, min. | 0.2 mm ² |
| Wire cross-section stranded with wire-end ferrules, max. | 1.5 mm ² |
| Wire cross-section AWG, min. | 24 |
| Wire cross-section AWG, max. | 16 |
| Stripping length | 12 mm |

Materials

| | |
|---------------------------|---------------|
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-0 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 120 °C |

Data sheet

3201.5 FRK 1,5/3A BU



Technical data

Further technical data

| | |
|-------------------------------------|-------------------------|
| Mounting type | Mounting rail TS 35/7,5 |
| Gauge plug acc. to EN 60 947-1 | A1 |
| Number of cross-connection channels | 2 |
| End plate required | ✓ |

Environmental Product Compliance

| | |
|--------------------------------|-----|
| REACH Conform | Yes |
| REACH Candidate Substance Note | No |
| RoHS Conform | Yes |

Approvals

Standards and regulations

| | |
|----------------------|----------------|
| EAC approval | TR ZU 004/2011 |
| EAC approval granted | yes |

CSA approval

| | |
|----------------------------------|--------------|
| CSA approval | C22.2 No 158 |
| CSA approval granted | yes |
| CSA Usegroup C: rated voltage | 600 V |
| CSA Usegroup C: rated current | 16 A |
| CSA wire cross-section AWG, min. | 24 |
| CSA wire cross-section AWG, max. | 16 |
| CSA stripping length | 12 mm |



CSAus approval

| | |
|------------------------------------|---------|
| CSAus approval | UL 1059 |
| CSAus approval granted | yes |
| CSAus Usegroup C: rated voltage | 600 V |
| CSAus Usegroup C: rated current | 16 A |
| CSAus wire cross-section AWG, min. | 24 |
| CSAus wire cross-section AWG, max. | 16 |
| CSAus stripping length | 12 mm |

KEMA KEUR approval

| | |
|---|---------------------|
| KEMA KEUR approval | EN 60947-7-1:2009 |
| KEMA KEUR approval granted | yes |
| KEMA rated voltage | 800 V |
| KEMA rated current | 17,5 A |
| KEMA rated impulse voltage | 8 kV |
| KEMA wire cross-section single core (rigid), min. | 0.2 mm ² |
| KEMA wire cross-section single-core (rigid), max. | 1.5 mm ² |
| KEMA wire cross-section stranded, min. | 0.2 mm ² |
| KEMA wire cross-section stranded, max. | 1.5 mm ² |

Media



Accessories

End plate

End plate, Width: 1.5 mm, Colour: Beige



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------|---------------|----------------|
| <u>3401.2</u> | FAP 1,5/3A BG | 4044211112608 | 20 |

End stop

End stop, Mounting type: Mounting rail TS 35/7.5 and TS 35/15, Width: 5 mm, Colour: Beige



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3811.2</u> | ZES 35/2 BG | 4044211080600 | 50 |

Insulated cross-connector

Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 8.1 mm, Colour: Yellow



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3452.8</u> | FQI 1,5/2 YE | 4044211110642 | 50 |

Insulated cross-connector, No. of poles: 5, Mounting type: Plug in, Width: 20.4 mm, Colour: Yellow



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3455.8</u> | FQI 1,5/5 YE | 4044211110673 | 20 |

Insulated cross-connector, No. of poles: 6, Mounting type: Plug in, Width: 24.5 mm, Colour: Yellow



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3456.8</u> | FQI 1,5/6 YE | 4044211110697 | 20 |

Insulated cross-connector



Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 40.9 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------|---------------|----------------|
| <u>3450.8</u> | FQI 1,5/10 YE | 4044211110635 | 10 |



Insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 12.2 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3453.8</u> | FQI 1,5/3 YE | 4044211110659 | 50 |



Insulated cross-connector, No. of poles: 8, Mounting type: Plug in, Width: 32.7 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3458.8</u> | FQI 1,5/8 YE | 4044211110703 | 10 |



Insulated cross-connector, No. of poles: 9, Mounting type: Plug in, Width: 36.8 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3459.8</u> | FQI 1,5/9 YE | 4044211110710 | 10 |



Insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 16.3 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3454.8</u> | FQI 1,5/4 YE | 4044211110666 | 20 |



Insulated cross-connector, No. of poles: 7, Mounting type: Plug in, Width: 28.6 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3457.8</u> | FQI 1,5/7 YE | 4044211127985 | 20 |

Data sheet

3201.5 FRK 1,5/3A BU

Quick marking



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 4 mm, Colour: White

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>4820.7</u> | PMC SB 4/50 WH | 4044211112127 | 500 ST |

Four-way cover



Cover, Length: 3.4 mm, Width: 15.7 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>3425.8</u> | FAD 1,5/4/B YE | 4044211132910 | 20 ST |