



HARTING P/N	REVISION	Cable length (L)
3315 243 010 0004	02	100 ± 3
3315 243 020 0005	02	200 ± 3
3315 243 050 0006	02	500 ± 5
3315 243 060 0006	00	600 ± 10
3315 243 070 0006	00	700 ± 10
3315 243 030 0006	00	300 ± 5
3315 243 005 0006	00	50 ± 3
3315 243 013 0006	00	130 ± 3
3315 243 015 0006	00	150 ± 3
3315 244 255 0006	00	255 ± 3
3315 243 007 0435	00	70 ± 3

WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
11	AWG 30	11
12	AWG 30	12

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT(500VDC)TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE
HARTING P/N

	All Dimensions in mm	Tech. Character.	Free size tol.	According to production drawing
	All rights reserved	Created by LINI Lin	Inspected by LIANL Lian	Standardisation LIANL Lian
	Department HCS - CN	Date 2021-11-29		State Final Release
HARTING Customised Solutions D-32339 Espelkamp		Title Har-Flex 12 Pole,Dul-end,With SR,L=XX MM		Doc-Key / ECM-Nr. 100586793/UGD/000/J 50000207144
		Type TB	Number 33150002	Rev. J Page 1/1