

C1 HAR-FLEX 26 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

C2 HAR-FLEX 26 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

WIRING TABLE

| C1 | WIRE | C2 |
|----|--------|----|
| 1 | AWG 30 | 1 |
| 2 | AWG 30 | 2 |
| 3 | AWG 30 | 3 |
| - | AWG 30 | - |
| 25 | AWG 30 | 25 |
| 26 | AWG 30 | 26 |

| HARTING P/N | REVISION | Cable length (L) |
|-------------------|----------|--------------------|
| 3315 243 006 0007 | 00 | 60 ± 3 |
| 3315 243 010 0007 | 02 | 100 ± 3 |
| 3315 243 020 0008 | 02 | 200 ± 3 |
| 3315 243 050 0009 | 02 | 500 ± 5 |
| 3315 243 027 0034 | 02 | 270 ± 5 |
| 3315 243 030 0034 | 00 | 300 ± 5 |
| 3315 243 060 0034 | 00 | 600 ± 10 |
| 3315 243 100 0034 | 00 | 1000 ± 10 |
| 3315 243 012 0034 | 00 | 120 ± 3 |
| 3315 243 017 0034 | 00 | 170 ± 3 |
| 3315 244 065 0034 | 00 | 65 ± 3 |
| 3315 244 380 0034 | 00 | 380 ± 5 |

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT(500VDC)TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:


DATA CODE
HARTING P/N

| | | | | | | | |
|---|---------------------|---|-------------------------------|---|--------------------|------------------------|----------|
| | All rights reserved | Created by LINI Lin | Inspected by LIANL Lian | Standardisation LIANL Lian | Date 2021-08-13 | State Final Release | Ref. \ |
| | Department HCS - CN | Title Har-Flex 26 Pole,Dul-end,With SR,L=XX MM | | Doc-Key / ECM-Nr. 100587128/UGD/000/J 50000201051 | | Rev. J | Page 1/2 |
| HARTING Customised Solutions D-32339 Espelkamp | | Type TB | Number 33150003 | | | | |

| 1 | | 2 | | 3 | | 4 | | |
|------|------|-------|------|-----------------------|--------------------------------------|----|------|------|
| Rev. | Loc. | Sheet | Date | Description of change | | Cb | Ib | |
| A | G | D6,D7 | 1 | 2017-08-09 | Add cable length 170mm via CRZ1742B. | | Z.L. | W.E. |
| | | - | 1-2 | | add sheet2 for revision history | | | |
| | H | E6 | 1 | 2018-05-29 | Add cable length 65mm via CRZ1908A. | | L.I. | Q.L. |
| | | E6 | 1 | 2018-06-20 | Add cable length 380mm via CRZ1917A. | | | |
| | | E6 | 1 | 2020-03-23 | Add cable length 60mm via CRZ2095A. | | | |
| B | J | E6 | 1 | 2021-08-06 | Add cable length 300mm via CRZ2240A. | | Z.D. | L.K. |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| C | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

D

E

| | | | | | | | | |
|---|---|----------------------|---|-------------------------------|----------------------------------|--------------------|--|--|
| F |  | All Dimensions in mm | Tech. Character. | | Free size tol. | | According to production drawing | |
| | All rights reserved | | Created by LINI Lin | Inspected by LIANL Lian | Standardisation LIANL Lian | Date 2021-08-13 | State Final Release | |
| | Department HCS - CN | | Title Har-Flex 26 Pole,Dul-end,With SR,L=XX MM | | | | Doc-Key / ECM-Nr. 100587128/UGD/000/J 500000201051 | |
| HARTING Customised Solutions D-32339 Espelkamp | | | Type TB | Number 33150003 | | Rev. J | Page 2/2 | |