



C1 HAR-FLEX 32 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

FLAT CABLE,UL2678,AWG30,32CORE

C2 HAR-FLEX 32 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
31	AWG 30	31
32	AWG 30	32

HARTING P/N	Cable length (L)
3315 243 010 0010	100 ± 3
3315 243 020 0011	200 ± 3
3315 243 050 0012	500 ± 5
3315 243 030 0012	300 ± 5

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT TEST.
- 2.)CABLE OPERATION TEMPERATURE:-20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG, THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATE COD
HARTING P/N

Coating \	A=	\ mm ²	V=	\ mm ³	m=	\ g	Mat. See bill of materials
	All Dimensions in mm Original Size DIN A3		Scale 2:1	Free size tol. \		Ref. \ Sub. \	
	All rights reserved Department HCS - CN		Created by LIN Lin	Inspected by QINL Qin	Standardisation QINL Qin	Date 2020-03-30	State Final Release
HARTING Customised Solutions D-32339 Espelkamp			Title Har-Flex 32 Pole,Dul-end,With SR,L=XX MM		Doc-Key / ECM-Nr. 100881312/UGD/000/D 500000166672		Rev. D Page 1/2
			Type TB	Number 33 15 00 04			

