



C1 HAR-FLEX 68 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

WHITE LABEL

FLAT CABLE, UL2678, AWG30.68CORE

C2 HAR-FLEX 68 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
67	AWG 30	67
68	AWG 30	68

HARTING P/N	Cable length(L)
3315 243 010 0122	100 ± 3
3315 243 020 0122	200 ± 5
3315 243 050 0122	500 ± 10

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT(500VDC)TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG, THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE & LOT INFORMATION  
HARTING P/N & REVISION

	All rights reserved Department HCS - CN HARTING Customised Solutions D-32339 Espelkamp	All Dimensions in mm Original Size DIN A3	Scale 1.5:1	Free size tol.	Ref. \
		Created by ZHENGL	Inspected by WANGE	Standardisation CHENJU	Date 2018-10-12
Title Har-Flex 68Pole,Dul-end,With SR,L=XXMM					Doc-Key / ECM-Nr. 100586962/UGD/000/A 50000014.1225
Type TB		Number 33150023		Rev. A	Page 1/1