



C1 HAR-FLEX 100 POLE FEMALE CONNECTOR FLAT CABLE,UL2678,AWG30.100CORE WITH STRAIN RELIEF

C2 HAR-FLEX 100 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
99	AWG 30	99
100	AWG 30	100

HARTING P/N	Cable length(L)
3315 243 010 0124	100 ± 3
3315 243 020 0124	200 ± 3
3315 243 033 0124	330 ± 5
3315 243 050 0124	500 ± 5
3315 243 080 0124	800 ± 10
3315 243 090 0124	900 ± 10
3315 243 100 0124	1000 ± 10

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT(500VDC)TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE & LOT INFORMATION
HARTING P/N & REVISION

	All rights reserved Department HCS - CN HARTING Customised Solutions D-32339 Espelkamp	All Dimensions in mm Original Size DIN A3	Scale 1.5:1	Free size tol.	Ref. \
		Created by ZHENGL	Inspected by WANGE	Standardisation CHENJU	Date 2018-10-12
Title Har-Flex 100 Pole,Dul-end,With SR,L=XXMM					Doc-Key / ECM-Nr. 100587005/UGD/000/B 50000014.1237
Type TB		Number 33150025		Rev. B	Page 1/1