



HAR-FLEX 12 POLE FEMALE CONNECTOR

HAR-FLEX 12 POLE FEMALE CONNECTOR

WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
11	AWG 30	11
12	AWG 30	12

HARTING P/N	Cable length (L)
33152430100145	100±3
33152430200145	200±5
33152430300145	300±5
33152430500145	500±5

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG, THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE  
HARTING P/N

	All rights reserved	Created by LINI Lin	Inspected by QINL Qin	Standardisation QINL Qin	Date 2019-08-09	State Final Release	Ref. \
	Department HCS - CN	Title Har-Flex 12 Pole, Dul-end, W/O SR, L=XX MM		Doc-Key / ECM-Nr. 100598240/UGD/000/A 500000156477		Rev. A	Page 1/1
HARTING Customised Solutions D-32339 Espelkamp		Type TB	Number 33150028				