



WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
49	AWG 30	49
50	AWG 30	50

HARTING P/N	LENGTH (L)
33152430100384	100±3
33152430200384	200±5
33152430500384	500±5

HAR-FLEX 50P FEMALE CONNECTOR WITH STRAIN RELIEF

HAR-FLEX 50P FEMALE CONNECTOR WITH STRAIN RELIEF

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE
HARTING P/N

	All rights reserved Department HCS - CN	Created by LIN Lin	Inspected by QINL Qin	Standardisation QINL Qin	Date 2019-08-03	State Final Release	According to production drawing
HARTING Customised Solutions D-32339 Espelkamp		Title Har-flex 50Pole,Dul-end,With SR,L=XXMM		Doc-Key / ECM-Nr. 100835287/UGD/000/A 500000156106		Rev. A	Page 1/1
		Type TB	Number 33 15 243 XXX0384				