



RJI RJ45 GL Compact plug, Cat. 6A, 8-pole
Protection level: IP20

HARTING PushPull Gigalink, Cat. 6A, overmolded
Protection level: IP67/65

Mating face RJ45 acc. to IEC 60603-7

RJI Ethernet stranded cable,
AWG 26/7, 2x4x0.5/1.0, outdoor,
Cat. 6A, PVC, black

Loading-Plan
acc. to TIA/EIA 568B

Shield	
1	White/Orange
2	Orange
3	White/Green
4	Blue
5	White/Blue
6	Green
7	White/Brown
8	Brown

- Temperature range: -20°C ... +70°C

20	3345421020003	20
19	33454210190003	19
18	33454210180003	18
17	33454210170003	17
16	33454210160003	16
15	33454210150003	15
14	33454210140003	14
13	33454210130003	13
12	33454210120003	12
11	33454210110003	11
10	33454210100003	10
9	33454210090003	9
8	33454210080003	8
7	33454210070003	7
6	33454210060003	6
5	33454210050003	5
4	33454210040003	4
3	33454210030003	3
2	33454210020003	2
1	33454210010003	1

Cont. no.	Part no.	Type of cable	Dim. a[m]
-----------	----------	---------------	-----------

		All Dimensions in mm Original Size DIN A3		Scale 2:1		Free size tol.		Ref.	
All rights reserved Department EC PD - RO		Created by MUNTEANV		Inspected by AVRAM		Standardisation HOFFMANN		Date 2015-05-20	
HARTING Electronics GmbH D-32339 Espelkamp		Title HARTING PushPull RJ45 Cable Assembly				Doc-Key / ECM-Nr. 100223972/UGD/007/B 50000089209		State Final Release	
		Type TB		Number 3345421XXX0003		Rev. B		Page 1/1	