



ELECTRICAL TESTING

TEST	L	Z
# TURNS	1 BOTH HOLES	1 BOTH HOLES
TEMPERATURE	25 °C	-
AWG	18 200mm LG	18 200mm LG
FREQUENCY	100 KHZ	10 MHZ
NOMINAL	10 uH	154 Ω (Ref.)
MINIMUM	7.5 uH	- Ω
MAXIMUM	12.5 uH	- Ω

WEIGHT/1000 1.46 kgs [3.23 Lbs]

COATING SPECIFICATIONS			TEST FORCE (LB)
THK. (MILS)	MIN DLB		
35N0372-00P UNCOATED	-	-	-
35N0372-00P PARYLENE	0.5	1000 VDC	0.62

UNCONTROLLED DOCUMENT

THIS DOCUMENT CONTAINS INFORMATION WHICH IS PROPRIETARY AND CONFIDENTIAL TO STEWARD. NO PRODUCTION OR PUBLICATION OF THIS DOCUMENT IN WHOLE OR IN PART SHALL BE MADE WITHOUT WRITTEN AUTHORIZATION FROM STEWARD.



PROJECT/PART NUMBER: 35N0372-00P
REV: B
DRAWN BY: Jccl

DATE: 02/25/2009
SCALE:
MATERIAL: STEWARD 35

REV	DESCRIPTION	DATE	INT
B	Change the L spec	02/25/09	Jccl
A	ORIGINAL DRAFT	04/29/07	Dxu

BARE DIMENSIONS:

	35N0372-000	35N0372-00P
A	9.40 [.370]	0.35 [.014]
B	5.35 [.211]	0.15 [.006]
C	8.00 [.315]	0.25 [.010]
D	2.59 [.102]	0.13 [.005]
E	5.24 [.206]	0.10 [.004]
F	2.62 [.103]	0.05 [.002]
G	0.75 [.030]	0.25 [.010]
		0.00 [.000]
<u>Single PARYLENE COATING</u>		
A	9.43 [.371]	0.35 [.014]
B	5.37 [.211]	0.15 [.006]
C	8.03 [.316]	0.25 [.010]
D	2.57 [.101]	0.13 [.005]
E	5.24 [.206]	0.10 [.004]
F	2.62 [.103]	0.05 [.002]
G	0.75 [.030]	0.25 [.010]
		0.00 [.000]

DIMENSIONS ARE IN mm [INCHES].